

## NETGEAR ProSAFE Smart Switch - GS748T - 48 Poorten

**Merk :** NETGEAR

**Artikelcode:** GS748T-500EUS



**Productnaam :** ProSAFE Smart Switch - GS748T - 48 Poorten

NETGEAR ProSAFE Smart Switch - GS748T - 48 Poorten. Switch type: Managed, Switch-laag: L2+. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 48. Full duplex. MAC-adrestabel: 8000 entries. Netwerkstandaard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Netstekker: DC-in ingang. Rack-montage

Beheerfuncties		Design	
Switch type *	Managed	Certificering	CE mark, commercial FCC Part 15 Class A VCCI Class A EN 55022 (CISPR 22), Class A EN 50082-1 EN 55024 C-Tick
Switch-laag	L2+		
Quality of Service (QoS)	✓		
Web-gebaseerd management	✓		
Poorten & interfaces		Prestatie	
Aantal basis-switching RJ-45 Ethernet-poorten *	48	Compatibele besturingssystemen	Windows, MAC, Linux
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Geluidsniveau	52 dB
Aantal Combo SFP-poorten	2	Mean time between failures (MTBF)	108000 uur
Aantal moduleslots SPF	2		
Netstekker	DC-in ingang	Energie	
Netwerk		Stroombron *	AC
Netwerkstandaard *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	AC-ingangsspanning	100 - 240 V
10G support *	✗	AC-ingangsfrequentie	50 - 60 Hz
Full duplex	✓	Stroomverbruik (typisch)	66 W
Datastroombeheer	✓	Vermogensverbruik (max)	70 W
Verbindingsaggregatie	✓	Power over Ethernet (PoE)	
Rate limiting	✓	Power over Ethernet (PoE) *	✗
Spanning tree protocol	✓	Eisen aan de omgeving	
VLAN=ondersteuning	✓	Bedrijfstemperatuur (T-T)	0 - 40 °C
Aantal VLANs	64	Temperatuur bij opslag	-10 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	0 - 90 procent
MAC-adrestabel *	8000 entries	Luchtvochtigheid bij opslag	0 - 95 procent
Latentie (10-100 Mbps)	20 µs	Hoogte, in bedrijf	0 - 3000 m
Jumbo Frames ondersteuning	✓	Hoogte bij opslag	0 - 3000 m
Packet buffergeheugen	1,632 MB	Gewicht en omvang	
Beveiliging		Breedte	305 mm
DHCP-functies	DHCP client	Diepte	43 mm
Access Control List (ACL)	✓	Hoogte	440 mm
Design		Gewicht	4,9 kg
Rack-montage *	✓	Verpakking	
Kleur van het product	Blauw	Meegeleverde kabels	LAN (RJ-45)
Veiligheid	UL listed (UL 1950)/cUL, IEC 950/EN 60950	Snelstartgids	✓
		Gebruiksaanwijzing	✓
		Gebruikershandleiding	✓
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 85176990	



0606449098242



606449098242



4056572857340

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.