

GIGABYTE AORUS ELITE P1000W power supply unit 1000 W 20+4 pin ATX ATX Zwart

Merk : GIGABYTE

Artikelcode: GP-AE1000PM PG5 EU

Productnaam : AORUS ELITE P1000W

GIGABYTE AORUS ELITE P1000W. Totaal vermogen: 1000 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 65 cm, Bekabelingstype: Volledig modulair. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Platinum. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Breedte: 150 mm, Diepte: 140 mm, Hoogte: 86 mm



Energie		Poorten & interfaces	
Totaal vermogen *	1000 W	ATX power connector (20+4 pin)	✓
AC-ingangsspanning *	100 - 240 V	Floppy drive power connector	2
AC-ingangsfrequentie	50/60 Hz	Aansluiting voor diskettestation	✓
Stroom	15 - 6.5 A	PCI Express connector	✓
Power factor	0,9	Bekabelingstype	Volledig modulair
Power Factor Correctie (PFC) type	Actief	Prestatie	
Gecombineerd vermogen (+3.3V)	125 W	80 PLUS certificatie *	80 PLUS Platinum
Gecombineerd vermogen (+12V)	999,6 W	Bedoeld voor *	PC
Gecombineerd vermogen (+5V)	125 W	Vormfactor van de voeding (PSU) *	ATX
Gecombineerd vermogen (-12V)	3,6 W	ATX version	3.1
Gecombineerd vermogen(+5Vsb)	15 W	Bearing technologie	Kogellager
Max huidige output (+3.3V)	25 A	Mean time between failures (MTBF)	100000 uur
Max huidige output(+12V)	83,3 A	Design	
Max huidige output (+5V)	25 A	Kleur van het product	Zwart
Max huidige output (-12V)	0,3 A	Type koeling	Actief
Max huidige output (+5Vsb)	3 A	Ventilator diameter	12 cm
Houd-tijd	16 ms	Aantal ventilatoren	1 ventilator(en)
Efficientie	92 procent	Ventilator locatie	Boven
Vertragingsbereik Power Good-sig-naal	100 - 150 ms	Aan/uitschakelaar	✓
Stroomspanning bescherming	Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Kortsluiting, Onder spanning	Gewicht en omvang	
Poorten & interfaces		Breedte	150 mm
Motherboard power connector *	20+4 pin ATX	Diepte	140 mm
Lengte stroomkabel moederbord	65 cm	Hoogte	86 mm
Aantal SATA power connectors	6	Gewicht	3,08 kg
Peripheral (Molex) power connectors (4-pin) *	4	Verpakking	
PCI Express power connectors (6+2 pin)	6	Breedte verpakking	340 mm
CPU power connector (4+4 pin)	✓	Diepte verpakking	206 mm
		Hoogte verpakking	120 mm
		Gewicht verpakking	3,72 kg
		Type verpakking	Doos

Technische details

Garantieperiode	10 jaar
-----------------	---------



4719331554521

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-OCT-2024. Prints or copies of Information are only valid on the printed Publication date