

ASUS Prime AP-750G power supply unit 750 W 20+4 pin ATX ATX Zwart, Wit

Merk : ASUS

Productfamilie: Prime

Artikelcode: 90YE00U1-
B0NA00

Productnaam : AP-750G

ASUS Prime AP-750G. Totaal vermogen: 750 W, AC-ingangsspanning: 100 - 240 V, Power Factor Correctie (PFC) type: Actief. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 61 cm, Lengte SATA-stroomkabel: 120,400 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Wit, Type koeling: Actief. Meegeleverde kabels: AC, CPU, PCIe, Peripheral (Molex), SATA



Energie		Poorten & interfaces	
Totaal vermogen *	750 W	CPU power connector (4+4 pin)	✓
AC-ingangsspanning *	100 - 240 V	Lengte CPU-stroomkabel	65 cm
Power Factor Correctie (PFC) type	Actief	ATX power connector (20+4 pin)	✓
Gecombineerd vermogen (+3.3V)	110 W	Bekabelingstype	Volledig modulair
Gecombineerd vermogen (+12V)	744 W	Prestatie	
Gecombineerd vermogen (+5V)	110 W	80 PLUS certificatie *	80 PLUS Gold
Gecombineerd vermogen (-12V)	3,6 W	Bedoeld voor *	PC
Gecombineerd vermogen(+5Vsb)	12,5 W	Vormfactor van de voeding (PSU) *	ATX
Max huidige output (+3.3V)	20 A	ATX version	3.0
Max huidige output(+12V)	62 A	Bearing technologie	Kogellager
Max huidige output (+5V)	20 A	Mean time between failures (MTBF)	120000 uur
Max huidige output (-12V)	0,3 A	Design	
Max huidige output (+5Vsb)	2,5 A	Kleur van het product	Zwart, Wit
Efficiëntie	92 procent	Type koeling	Actief
Stroomspanning bescherming	Te hoog vermogen, Overspanning, Overbelasting, Oververhitting, Kortsluiting, Onder spanning	Aan/uitschakelaar	✓
Poorten & interfaces		Inhoud van de verpakking	
Motherboard power connector *	20+4 pin ATX	Meegeleverde kabels	AC, CPU, PCIe, Peripheral (Molex), SATA
Lengte stroomkabel moederbord	61 cm	Gewicht en omvang	
Aantal SATA power connectors	5	Breedte	150 mm
Lengte SATA-stroomkabel	120,400 mm	Diepte	150 mm
Peripheral (Molex) power connectors (4-pin) *	3	Hoogte	86 mm
Lengte stroomkabel randapparaat (Molex)	150,400 mm	Gewicht	1,47 kg
PCI Express power connectors (8-pin)	3	Verpakking	
PCI Express-voedingsconnectoren (16-pins)	1	Breedte verpakking	346 mm
		Diepte verpakking	208 mm

Poorten & interfaces		Verpakking	
CPU P4 connector (4-pin)	2	Hoogte verpakking	144 mm
		Gewicht verpakking	2,88 kg
		Type verpakking	Doos



4711387192962



0197105193031



197105193031



0197105192966



197105192966

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.