




DeepCool PL650D power supply unit 650 W 20+4 pin ATX ATX Zwart

Merk : DeepCool

Artikelcode: R-PL650D-FC0B-EU

Productnaam : PL650D

DeepCool PL650D. Totaal vermogen: 650 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 55 cm, Lengte SATA-stroomkabel: 550,450,650 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Bronze. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Certificaten van naleving: RoHS, WEEE, Certificering: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH



Energie		Poorten & interfaces	
Totaal vermogen *	650 W	ATX power connector (20+4 pin)	✓
AC-ingangsspanning *	100 - 240 V	Bekabelingstype	Niet-modulair
AC-ingangsfrequentie	50/60 Hz	Prestatie	
Stroom	9 - 4.5 A	80 PLUS certificatie *	80 PLUS Bronze
Power Factor Correctie (PFC) type	Actief	Bedoeld voor *	PC
Gecombineerd vermogen (+3.3V)	100 W	Vormfactor van de voeding (PSU) *	ATX
Gecombineerd vermogen (+12V)	648 W	ATX version	3.0
Gecombineerd vermogen (+5V)	100 W	Bearing technologie	HYB
Gecombineerd vermogen (-12V)	3,6 W	Mean time between failures (MTBF)	100000 uur
Gecombineerd vermogen(+5Vsb)	15 W	Design	
Max huidige output (+3.3V)	20 A	Kleur van het product	Zwart
Max huidige output(+12V)	54 A	Type koeling	Actief
Max huidige output (+5V)	20 A	Ventilator diameter	12 cm
Max huidige output (-12V)	0,3 A	Aantal ventilatoren	1 ventilator(en)
Max huidige output (+5Vsb)	3 A	Ventilator locatie	Boven
Houd-tijd	16 ms	Aan/uitschakelaar	✓
Efficiëntie	85 procent	Eisen aan de omgeving	
Vertragsbereik Power Good-sig-naal	100 - 150 ms	Bedrijfstemperatuur (T-T)	0 - 40 °C
Stroomspanning bescherming	No load operation, Overstroom, Te hoog vermogen, Overspanning, Oververhitting, Surge & inrush protection (SIP), Overspanningsbeveiliging, Onder spanning	Certificaten	
Poorten & interfaces		Certificaten van naleving	RoHS, WEEE
Motherboard power connector *	20+4 pin ATX	Certificering	CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH
Lengte stroomkabel moederbord	55 cm	Gewicht en omvang	
Aantal SATA power connectors	6	Breedte	150 mm
Lengte SATA-stroomkabel	550,450,650 mm	Diepte	140 mm
		Hoogte	86 mm

Poorten & interfaces		Verpakking	
Peripheral (Molex) power connectors (4-pin) *	2	Type verpakking	Doos
PCI Express power connectors (6+2 pin)	3	Technische details	
PCI Express-voedingsconnectoren (16-pins)	1	Naleving van duurzaamheid	✓
CPU power connector (4+4 pin)	✓	Duurzaamheidscertificaten	ErP, Triman
		Logistieke gegevens	
		Land van herkomst	China



6933412717874

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-JUN-2025. Prints or copies of Information are only valid on the printed Publication date