

DIGITUS® CAT 6A U-FTP twisted pair installation cable

DK-1623-A-VH-1 4016032344117



DIGITUS CAT 6A U-FTP installation cable, raw
Length 100 m, Paper Box, LSOH, AWG 23, Simplex, Color light blue RAL 5012

Best performance and link quality for your network

DIGITUS® Category 6A U-FTP installation cables are manufactured and tested to the ISO/IEC 11801, TIA-586-C.2 and EN 50173 Category 6A specifications. Every cord consists of 8 color coded AWG 23 Polyethylene insulated conductors. The conductors are twisted together to form 4 pairs with varying lay lengths. Printing details along the outer sheath includes the brand name and item code. The cable is packed in a paper pullout box or on a wooden drum which makes the installation easy.

- 1 25 Year System Warranty
- 1 Halogen free outer sheath
- 1 Category 6A compliant, ISO/IEC 11801, TIA-586-C.2, EN 50173
- 1 Stressless paper pullout box
- 1 AWG 23 conductor
- 1 500 MHz
- 1 Basic conductor: Solid AWG 23/1
- 1 Insulation: SFS-PE
- 1 Total number of insulated conductors: 8, twisted in 4 pairs
- 1 Color code: blue-white, orange-white, green-white, brown-white
- 1 Individual pair shielding: aluminum foil, providing 100% coverage
- 1 Overall shielding: none
- 1 Outer jacket: LSOH
- 1 Storage temperature: -20 to +60°C
- 1 Installation temperature: 0 to +50°C
- 1 Standard of flame retardancy: IEC 60332-1-1 (1,2)(2004-07)
- 1 Color: Light blue
- 1 Category: CAT 6A
- 1 Cable jacket: LSOH
- 1 Color: light-blue
- 1 Length: 100 m

DIGITUS® CAT 6A U-FTP twisted pair installation cable

DK-1623-A-VH-1 4016032344117

→ **Logistics**

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0,00	0,00	0,00	0,00	0,00
Packaging Unit Inside	1	0,00	0,00	0,00	0,00	0,00
Packaging Unit Single	1	0,00	0,00	0,00	0,00	0,00
Net single without Packaging	1	0,00	0,00	0,00	0,00	0,00

→ **Packaging type**



Country of origin: China