



XPG COREREACTOR II VE 850W power supply unit 24-pin ATX ATX Zwart

Merk : XPG

Artikelcode: 75261435

Productnaam : COREREACTOR II VE 850W

XPG COREREACTOR II VE 850W. Totaal vermogen: 850 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 47 - 63 Hz. Motherboard power connector: 24-pin ATX, Lengte stroomkabel moederbord: 65 cm, Lengte SATA-stroomkabel: 150,450 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Certificering: CB / CE / FCC / TUV / cTUVus / BSMI / CCC NOM / FCC IC / UKCA / TUV / TUV S-Mark / cTUVus



Energie		Poorten & interfaces	
Totaal vermogen *	850 W	CPU power connector (4+4 pin)	✓
AC-ingangsspanning *	100 - 240 V	Lengte CPU-stroomkabel	75 cm
AC-ingangsfrequentie	47 - 63 Hz	ATX Power connector (24-pin)	✓
Stroom	12 A	ATX-voedingsconnector (12+4-pins)	✓
Power factor	0,99	Bekabelingstype	Volledig modulair
Max huidige output (+3.3V)	20 A	Prestatie	
Max huidige output(+12V)	70,8 A	80 PLUS certificatie *	80 PLUS Gold
Max huidige output (+5V)	20 A	Bedoeld voor *	PC
Max huidige output (-12V)	0,3 A	Vormfactor van de voeding (PSU) *	ATX
Max huidige output (+5Vsb)	3 A	ATX version	3.1
Stroomspanning bescherming	Overstroom, Te hoog vermogen,	Bearing technologie	FDB
	Overspanning, Oververhitting, Kortsluiting, Surge & inrush protection (SIP), Onder spanning	Mean time between failures (MTBF)	100000 uur
Poorten & interfaces		Design	
Motherboard power connector *	24-pin ATX	Kleur van het product	Zwart
Lengte stroomkabel moederbord	65 cm	Type koeling	Actief
Aantal SATA power connectors	6	Ventilator diameter	12 cm
Lengte SATA-stroomkabel	150,450 mm	Aantal ventilatoren	1 ventilator(en)
Peripheral (Molex) power connectors (4-pin) *	2	Certificaten	
EPS power connector (8-pin)	✓	Certificering	
EPS-voedingsconnector (4+4 pin)	✓	CB / CE / FCC / TUV / cTUVus / BSMI / CCC NOM / FCC IC / UKCA / TUV / TUV S-Mark / cTUVus	
PCI Express power connectors (6+2 pin)	3	Gewicht en omvang	
Lengte van de PCI Express-voedingsconnectoren (12+4 pins)	600 mm	Breedte	150 mm
PCI Express voedingsconnectoren (12-pin)	1	Diepte	140 mm
		Hoogte	86 mm
		Gewicht	1,45 kg

Verpakking

Gewicht verpakking	3,03 kg
--------------------	---------



4711085946256



0842243032468



842243032468

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.