



# XPG COREREACTOR II 850W power supply unit 20+4 pin ATX ATX Wit

Merk : XPG

Artikelcode: 75261350

Productnaam : COREREACTOR II 850W

XPG COREREACTOR II 850W. Totaal vermogen: 850 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Bekabelingstype: Volledig modulair. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Wit, Type koeling: Actief, Ventilator diameter: 12 cm. Certificering: CE | CB| FCC(IC) | TUV | cTUVus | TUV S-Zeichen | NOM | BSMI | UKCA | EAC | CCC | RCM



| Energie                                       |                                                                                                                    | Prestatie                         |              |                                                                                             |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------------------|--------------|---------------------------------------------------------------------------------------------|
| Totaal vermogen *                             | 850 W                                                                                                              | 80 PLUS certificatie *            | 80 PLUS Gold |                                                                                             |
| AC-ingangsspanning *                          | 100 - 240 V                                                                                                        | Bedoeld voor *                    | PC           |                                                                                             |
| AC-ingangsfrequentie                          | 47 - 63 Hz                                                                                                         | Vormfactor van de voeding (PSU) * | ATX          |                                                                                             |
| Stroom                                        | 12 A                                                                                                               | ATX version                       | 3.0          |                                                                                             |
| Power factor                                  | 0,99                                                                                                               | EPS version                       | 2.92         |                                                                                             |
| Max huidige output (+3.3V)                    | 22 A                                                                                                               | Bearing technologie               | FDB          |                                                                                             |
| Max huidige output(+12V)                      | 62,5 A                                                                                                             | Mean time between failures (MTBF) | 100000 uur   |                                                                                             |
| Max huidige output (+5V)                      | 22 A                                                                                                               | <b>Design</b>                     |              |                                                                                             |
| Max huidige output (-12V)                     | 0,3 A                                                                                                              |                                   |              |                                                                                             |
| Max huidige output (+5Vsb)                    | 3 A                                                                                                                |                                   |              |                                                                                             |
| Stroomspanning bescherming                    | Overstroom, Te hoog vermogen,<br>Overspanning, Kortsluiting, Surge &<br>inrush protection (SIP), Onder<br>spanning |                                   |              |                                                                                             |
|                                               |                                                                                                                    |                                   |              |                                                                                             |
| Poorten & interfaces                          |                                                                                                                    | Kleur van het product             |              | Wit                                                                                         |
| Motherboard power connector *                 | 20+4 pin ATX                                                                                                       | Type koeling                      |              | Actief                                                                                      |
| Aantal SATA power connectors                  | 8                                                                                                                  | Ventilator diameter               |              | 12 cm                                                                                       |
| Peripheral (Molex) power connectors (4-pin) * | 4                                                                                                                  | Aantal ventilatoren               |              | 1 ventilator(en)                                                                            |
| EPS power connector (8-pin)                   | ✓                                                                                                                  | <b>Certificaten</b>               |              |                                                                                             |
| PCI Express power connectors (6+2 pin)        | 6                                                                                                                  |                                   |              |                                                                                             |
| ATX Power connector (24-pin)                  | ✓                                                                                                                  |                                   |              |                                                                                             |
| ATX-voedingsconnector (12+4-pins)             | ✓                                                                                                                  |                                   |              |                                                                                             |
| Bekabelingstype                               | Volledig modulair                                                                                                  |                                   |              |                                                                                             |
|                                               |                                                                                                                    | Certificering                     |              | CE   CB  FCC(IC)   TUV   cTUVus  <br>TUV S-Zeichen   NOM   BSMI   UKCA<br>  EAC   CCC   RCM |
|                                               |                                                                                                                    | <b>Gewicht en omvang</b>          |              |                                                                                             |
|                                               |                                                                                                                    | Breedte                           | 140 mm       |                                                                                             |
|                                               |                                                                                                                    | Diepte                            | 150 mm       |                                                                                             |
|                                               |                                                                                                                    | Hoogte                            | 86 mm        |                                                                                             |
|                                               |                                                                                                                    | Gewicht                           | 1,6 kg       |                                                                                             |
|                                               |                                                                                                                    | <b>Verpakking</b>                 |              |                                                                                             |
|                                               |                                                                                                                    | Gewicht verpakking                | 3,1 kg       |                                                                                             |



4711085944702



0842243031041



842243031041

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.