



XPG COREREACTOR II 1200W power supply unit 24-pin ATX ATX Zwart

Merk : XPG

Artikelcode: 75261221

Productnaam : COREREACTOR II 1200W

XPG COREREACTOR II 1200W. Totaal vermogen: 1200 W, AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz. Motherboard power connector: 24-pin ATX, Bekabelingstype: Volledig modulair. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Ventilator diameter: 13,5 cm. Certificaten van naleving: BSMI, CB, CE, China Compulsory Certification (CCC), EAC, Federal Communications Commission (FCC),..., Certificering: CE | CB| FCC(IC) | TUV | cTUVus | TUV S-Zeichen | NOM | BSMI | UKCA | EAC | CCC | RCM



Energie		Prestatie	
Totaal vermogen *	1200 W	80 PLUS certificatie *	80 PLUS Gold
AC-ingangsspanning *	100 - 240 V	Bedoeld voor *	PC
AC-ingangsfrequentie	50/60 Hz	Vormfactor van de voeding (PSU) *	ATX
Stroom	15 A	ATX version	3.0
Power factor	0,99	EPS version	2.92
Max huidige output (+3.3V)	22 A	Bearing technologie	FDB
Max huidige output(+12V)	100 A	Mean time between failures (MTBF)	100000 uur
Max huidige output (+5V)	22 A	Design	
Max huidige output (-12V)	0,3 A	Kleur van het product	Zwart
Max huidige output (+5Vsb)	3 A	Ventilator diameter	13,5 cm
Stroomspanning bescherming	Overstroom, Te hoog vermogen,	Certificaten	
	Overspanning, Oververhitting, Kortsluiting, Surge & inrush protection (SIP), Onder spanning	Certificaten van naleving	BSMI, CB, CE, China Compulsory Certification (CCC), EAC, Federal Communications Commission (FCC), Norma Oficial Mexicana (Mexicaanse norm, NOM), RCM, cTUVus, UKCA
Poorten & interfaces		Certificering	CE CB FCC(IC) TUV cTUVus TUV S-Zeichen NOM BSMI UKCA EAC CCC RCM
Motherboard power connector *	24-pin ATX	Gewicht en omvang	
Aantal SATA power connectors	9	Breedte	160 mm
Peripheral (Molex) power connectors (4-pin) *	3	Diepte	150 mm
EPS power connector (8-pin)	✓	Hoogte	86 mm
PCI Express power connectors (6+2 pin)	8	Verpakking	
ATX Power connector (24-pin)	✓	Breedte verpakking	210 mm
ATX-voedingsconnector (12+4-pins)	✓	Diepte verpakking	338 mm
Bekabelingstype	Volledig modulair	Hoogte verpakking	157 mm
		Gewicht verpakking	3,43 kg



4711085942401



0842243029437



842243029437

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.