



## ACT DA7901 netwerkkabel Zwart 1 m Cat6a U/FTP (STP)

**Merk :** ACT


**Artikelcode:** DA7901

**Productnaam :** DA7901


- Connectoren: RJ45 90° haaks beneden - RJ45 90° haaks boven
- Ideaal voor situaties met beperkte ruimte zonder de maximale buigradius van de kabel te overschrijden
- Volledig koperen 32AWG geleiders, 50µ vergulde RJ45 contacten
- Mantel met een buitendiameter van slechts 3,8mm voor een betere luchtstroom in de netwerkkast
- Low Smoke Zero Halogen (LSZH) kabelmantel reduceert het risico op het vrijkomen van schadelijke stoffen bij kabelschade door brand of kortsluiting
- Voldoet aan de internationale standaard
- Kabels zijn 100% getest

Zwarte 1 meter U/FTP CAT6A LSZH Slimline patchkabel met RJ45 connectoren 90° haaks beneden naar 90° haaks boven

ACT DA7901. Snoerlengte: 1 m, Kabel standaard: Cat6a, Kabelafscherming: U/FTP (STP), Aansluiting 1: RJ-45, Aansluiting 2: RJ-45, Contact geleider materiaal: Goud, Kleur van het product: Zwart



| Kenmerken                  |              | Kenmerken                                  |             |
|----------------------------|--------------|--------------------------------------------|-------------|
| Kleur van het product *    | Zwart        | AWG draad omvang                           | 32          |
| Snoerlengte *              | 1 m          | Frequentie                                 | 500 MHz     |
| Kabel standaard *          | Cat6a        | Krommingsstraal (min)                      | 1,5 cm      |
| Kabelafscherming *         | U/FTP (STP)  | Power over Ethernet (PoE)                  | ✓           |
| Aansluiting 1 *            | RJ-45        | Type Power over Ethernet (PoE) ondersteunt | PoE+        |
| Aansluiting 2 *            | RJ-45        | Totaal Power over Ethernet (PoE)-budget    | 30 W        |
| Aansluiting 1 type *       | Mannelijk    | <b>Eisen aan de omgeving</b>               |             |
| Aansluiting 2 type *       | Mannelijk    | Bedrijfstemperatuur (T-T)                  | -20 - 60 °C |
| Connector 1 vormfactor     | Haaks        | <b>Certificaten</b>                        |             |
| Connector 2 vormfactor     | Haaks        | Certificering                              | CE          |
| Contact geleider materiaal | Goud         | <b>Gewicht en omvang</b>                   |             |
| Materiaal buitenmantel     | Halogeenvrij | Outer diameter                             | 3,8 mm      |
| Geleidermateriaal          | Koper        |                                            |             |



8716065572209

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.