

TP-Link IES206GPP netwerk-switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Zwart

Merk : TP-Link

Artikelcode: IES206GPP

Productnaam : IES206GPP

TP-Link IES206GPP. Switch type: Managed. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 4. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 12 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE.... DC voltage input: 12 - 57 V. Power over Ethernet (PoE). Ophangstelsysteem voor aan de muur, Rack-montage



Beheerfuncties		Design	
Switch type *	Managed	Ophangstelsysteem voor aan de muur	✓
Poorten & interfaces		DIN rail bevestiging	✓
Aantal basis-switching RJ-45 Ethernet-poorten *	4	Prestatie	
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Fanloos	✓
Aantal Combo SFP-poorten	1	Energie	
Aantal moduleslots SPF	1	Stroombron *	DC/PoE
Netwerk		Redundante voeding	✓
Netwerkstandaard *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3x	DC voltage input	12 - 57 V
10G support *	✗	Power over Ethernet (PoE)	
Port mirroring	✓	Power over Ethernet (PoE) *	✓
Datastroombeheer	✓	Type Power over Ethernet (PoE) ondersteunt	PoE+, PoE++ (4PPoE)
Verbindingsaggregatie	✓	Aantal Power over Ethernet plus (PoE +)-poorten	3
Broadcast stormbeheer	✓	Aantal Power over Ethernet 4PPoE (PoE++)-poorten	1
Auto MDI/MDI-X	✓	Vermogen per poort Power over Ethernet (PoE)	30 W
Spanning tree protocol	✓	Totaal Power over Ethernet (PoE)-budget	120 W
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Eisen aan de omgeving	
Auto-negotiation	✓	Bedrijfstemperatuur (T-T)	-40 - 75 °C
		Temperatuur bij opslag	-40 - 85 °C

Data-uitwisseling		Eisen aan de omgeving	
Switchingcapaciteit *	12 Gbit/s	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Verzending snelheid	8,93 Mpps	Luchtvochtigheid bij opslag	5 - 95 procent
MAC-adrestabel *	8000 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	155 mm
Jumbo Frames ondersteuning	✓	Diepte	120 mm
Jumbo frames	15000	Hoogte	60 mm
Beveiliging		Inhoud van de verpakking	
DHCP-functies	DHCP client	Snelstartgids	✓
IGMP snooping	✓	Certificaten	
Multicast-functies		Certificering	FCC, CE, RoHS
Multicast-ondersteuning	✓		
Design			
Rack-montage *	✓		
Kleur van het product	Zwart		



1210002602051

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.