

TP-Link Omada EAP603-Outdoor 1800 Mbit/s Wit Power over Ethernet (PoE)

Merk : TP-Link

Productfamilie: Omada

Artikelcode: EAP603-OUTDOOR

Productnaam : EAP603-Outdoor

TP-Link Omada EAP603-Outdoor. 2,4 GHz, 5 GHz, Maximale overdrachtssnelheid van gegevens: 1800 Mbit/s. Ondersteunde beveiligingsalgoritmen: EAP, EAP-FAST, EAP-GTC, EAP-MD5, EAP-PEAP, EAP-SIM, EAP-TLS, EAP-TTLS, PEAP, PPSK, SNMP, SSH,.... Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Kleur van het product: Wit. Vermogensverbruik (max): 4,8 W



Kenmerken		Energie	
2,4 GHz *	✓	Power over Ethernet (PoE) *	✓
5 GHz *	✓	Type Power over Ethernet (PoE) ondersteunt	Passive PoE
6 GHz *	✗	DC voltage bereik	42.5 - 57 V
Maximale overdrachtssnelheid van gegevens *	1800 Mbit/s	Stroom	0.36 A
Maximale overdrachtssnelheid van gegevens (2.4 GHz)	573 Mbit/s	Vermogensverbruik (max)	4,8 W
Maximale overdrachtssnelheid van gegevens (5 GHz)	1201 Mbit/s	Design	
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Plaatsing *	Paal, Muur
Bluetooth	✓	Kleur van het product *	Wit
Maximum outdoorbereik	300 m	Internationale veiligheidscode (IP)	IP65, IP66
Beveiliging		Antenne	
Ondersteunde beveiligingsalgoritmen *	EAP, EAP-FAST, EAP-GTC, EAP-MD5, EAP-PEAP, EAP-SIM, EAP-TLS, EAP-TTLS, PEAP, PPSK, SNMP, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise, WPA3-Personal	Soort antenne *	Intern & extern
MAC adres filtering	✓	Type antennerichting	Omni-directioneel
IP-adresfilter	✓	Antennas quantity	4
Service Set Identifier (SSID) functies	Multiple SSIDs	Antenne versterkingsniveau (max)	5 dBi
Aantal SSID-ondersteuningen	16	Certificaten	
Toegang voor gasten	✓	Certificaten van naleving	CE, Federal Communications Commission (FCC), RoHS
Remote Authentication Dial-In User Service (RADIUS)	✓	Gewicht en omvang	
Access Control List (ACL)	✓	Breedte	230 mm
Beheerfuncties		Diepte	207,5 mm
Web-gebaseerd management	✓	Hoogte	69,7 mm
Cloud-beheerd	✓	Inhoud van de verpakking	
Backup-functie	✓	Inclusief PoE-adapter	✓
Poorten & interfaces		Montage gereedschap	✓
Aantal Ethernet LAN (RJ-45)-poorten *	1	Snelstartgids	✓
		Eisen aan de omgeving	
		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
		Bedrijfstemperatuur (T-T)	-30 - 70 °C
		Temperatuur bij opslag	-40 - 70 °C
		Luchtvochtigheid bij opslag	5 - 90 procent



1210002605731

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.