

TP-Link Omada ES210GP netwerk-switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) DIN rail Zwart



Merk : TP-Link

Productfamilie: Omada

Artikelcode: ES210GP

Productnaam : ES210GP

TP-Link Omada ES210GP. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 10. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 20 Gbit/s. Netwerkstandaard: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt. DC voltage input: 53 V. Power over Ethernet (PoE). Rack-montage, Vormfactor: DIN rail

Beheerfuncties		Beveiliging	
Switch type *	Managed	DHCP-functies	DHCP client
Switch-laag	L2	IGMP snooping	✓
Quality of Service (QoS)	✓	Bescherming lus	✓
Web-gebaseerd management	✓	Multicast-functies	
Cloud-beheerd	✓	Multicast-ondersteuning	✓
Poorten & interfaces		Design	
Aantal basis-switching RJ-45 Ethernet-poorten *	10	Rack-montage *	✓
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Vormfactor	DIN rail
Aantal Combo SFP-poorten	1	Kleur van het product	Zwart
Netwerk		LED-indicatoren	✓
Netwerkstandaard *	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt	Energie	
10G support *	✗	Stroombron *	DC
Port mirroring	✓	DC voltage input	53 V
Datastroombeheer	✓	Stroom	1.31 A
Verbindingsaggregatie	✓	Power over Ethernet (PoE)	
Broadcast stormbeheer	✓	Power over Ethernet (PoE) *	✓
Auto MDI/MDI-X	✓	Type Power over Ethernet (PoE) ondersteunt	PoE+
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Aantal Power over Ethernet plus (PoE +)-poorten	8
Auto-negotiation	✓	Totaal Power over Ethernet (PoE)-budget	63 W
VLAN=ondersteuning	✓	Eisen aan de omgeving	
Virtuele LAN-functies	MTU VLAN, Port-based VLAN, Tagged VLAN	Bedrijfstemperatuur (T-T)	0 - 40 °C
Aantal VLANs	4000	Temperatuur bij opslag	-40 - 70 °C
Optische vezel		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Transmissie afstand (max)	0,25 km	Luchtvochtigheid bij opslag	5 - 90 procent
Data-uitwisseling		Gewicht en omvang	
Switchingcapaciteit *	20 Gbit/s	Breedte	209 mm
Verzending snelheid	14,88 Mpps	Diepte	126 mm
MAC-adrestabel *	8000 entries	Hoogte	26 mm
Store-and-forward	✓	Inhoud van de verpakking	
Jumbo Frames ondersteuning	✓	Meegeleverde kabels	Stroom
Jumbo frames	15000	Snelstartgids	✓
Packet buffergeheugen	0,5 MB	Certificaten	
		Certificaten van naleving	CE, Federal Communications Commission (FCC), RoHS



1210002609722

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.