



Delock HDMI UHD Splitter 1 x HDMI in > 4 x HDMI out 4K

Description

This splitter by Delock receives a HDMI signal from a PC or laptop and splits it to four connected displays. Thereby one HDMI connection can be used to operate four HDMI monitors.



Specification

Connector:

Input:

1 x HDMI-A 19 pin female

1 x DC 5 V power connector

Output:

4 x HDMI-A 19 pin female

- High Speed HDMI specification
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- · Reset button
- · LED indicator
- Supports a resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Video bandwidth up to 600 MHz / 6 Gbps, 18 Gb/s max.
- Power consumption: max. 2.4 W
- · Metal housing
- · Colour: black
- Dimensions (LxWxH): ca. 123 x 51 x 20 mm

Power supply specification

- · Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- · Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

System requirements

- A free HDMI female port
- HDMI cable

Package content

- HDMI Splitter
- USB power cable
- · External power supply
- User manual

Item No. 18684

EAN: 4043619186846

Country of origin: China

Package: Retail Box







Images









| General | |
|----------------------------|-------------------------------------|
| Specification: | HDCP 1.4 |
| | HDCP 2.2 |
| | High Speed HDMI |
| Interface | |
| Input: | 1 x HDMI-A 19 pin female |
| | 1 x 5 V DC female 5,5 mm x 2,1 mm |
| Output: | 4 x HDMI-A 19 pin female |
| Technical characteristics | |
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |
| Video bandwidth: | 600 MHz / 6 Gbps |
| Physical characteristics | |
| Housing colour: | black |
| Housing: | metal |
| Length: | 123 mm |
| Width: | 51 mm |
| Height: | 20 mm |
| Power supply | |
| Type: | Euro wall power supply |
| Input: | AC 100 - 240 V / 50 - 60 Hz / 0.5 A |
| Output: | 5 V / 2 A |
| Connector: | DC male 5,5 mm x 2,1 mm |
| Cable length: | 1 m |