



## TP-Link Omada ES208GP netwerk-switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) DIN rail Zwart



**Merk :** TP-Link

**Productfamilie:** Omada

**Artikelcode:** ES208GP

**Productnaam :** ES208GP

TP-Link Omada ES208GP. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 8. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 16 Gbit/s. Netwerkstandaard: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt. DC voltage input: 53 V. Power over Ethernet (PoE). Rack-montage, Vormfactor: DIN rail

| Beheerfuncties                                  |  | Beveiliging                                     |   |
|---|--|---|---|
| Switch type *                                   | Managed                                  | IGMP snooping                                   | ✓   |
| Switch-laag                                     | L2                                       | Bescherming lus                                 | ✓   |
| Quality of Service (QoS)                        | ✓  | <b>Multicast-functies</b>                       |   |
| Web-gebaseerd management                        | ✓  | Multicast-ondersteuning                         | ✓   |
| Cloud-beheerd                                   | ✓  | <b>Design</b>                                   |   |
| <b>Poorten &amp; interfaces</b>                 |  | Rack-montage *                                  | ✓   |
| Aantal basis-switching RJ-45 Ethernet-poorten * | 8  | Vormfactor                                      | DIN rail  |
| Type basis-switching RJ-45 Ethernet-poorten *   | Gigabit Ethernet (10/100/1000)           | Kleur van het product                           | Zwart   |
| <b>Netwerk</b>                                  |  | LED-indicatoren                                 | ✓   |
| Netwerkstandaard *                              | IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt | <b>Energie</b>                                  |   |
| 10G support *                                   | ✗  | Stroombron *                                    | DC  |
| Port mirroring                                  | ✓  | DC voltage input                                | 53 V  |
| Datastroombeheer                                | ✓  | Stroom  | 1.31 A  |
| Verbindingsaggregatie                           | ✓  | <b>Power over Ethernet (PoE)</b>                |   |
| Broadcast stormbeheer                           | ✓  | Power over Ethernet (PoE) *                     | ✓   |
| Auto MDI/MDI-X                                  | ✓  | Type Power over Ethernet (PoE) ondersteunt      | PoE+  |
| Ethernet LAN, data-overdrachtsnelheden          | 10,100,1000 Mbit/s                       | Aantal Power over Ethernet plus (PoE +)-poorten | 8   |
| Auto-negotiation                                | ✓  | Totaal Power over Ethernet (PoE)-budget         | 64 W  |
| VLAN=ondersteuning                              | ✓  | <b>Eisen aan de omgeving</b>                    |   |
| Virtuele LAN-functies                           | MTU VLAN, Port-based VLAN, Tagged VLAN   | Bedrijfstemperatuur (T-T)                       | 0 - 40 °C   |
| Aantal VLANs                                    | 4000                                     | Temperatuur bij opslag                          | -40 - 70 °C                                       |
| <b>Optische vezel</b>                           |  | Relatieve vochtigheid in bedrijf (V-V)          | 10 - 90 procent                                   |
| Transmissie afstand (max)                       | 0,25 km                                  | Luchtvochtigheid bij opslag                     | 5 - 90 procent                                    |
| <b>Data-uitwisseling</b>                        |  | <b>Gewicht en omvang</b>                        |   |
| Switchingcapaciteit *                           | 16 Gbit/s                                | Breedte   | 158 mm  |
| Verzending snelheid                             | 11,904 Mpps                              | Diepte  | 100,7 mm  |
| MAC-adrestabel *                                | 8000 entries                             | Hoogte  | 25,4 mm   |
| Store-and-forward                               | ✓  | <b>Inhoud van de verpakking</b>                 |   |
| Jumbo Frames ondersteuning                      | ✓  | Meegeleverde kabels                             | Stroom  |
| Jumbo frames                                    | 15000                                    | Snelstartgids                                   | ✓   |
| Packet buffergeheugen                           | 0,5 MB                                   | <b>Certificaten</b>                             |   |
| <b>Beveiliging</b>                              |  | Certificaten van naleving                       | CE, Federal Communications Commission (FCC), RoHS |
| DHCP-functies                                   | DHCP client                              |   |   |



1210002609708



1210002609715



0840460603607



840460603607

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.