

StarTech.com MCM1110SMLC40 netwerk media converter 2000 Mbit/s 1310 nm Single-mode Zwart

Merk : StarTech.com

Artikelcode: MCM1110SMLC40

Productnaam : MCM1110SMLC40

StarTech.com MCM1110SMLC40. Maximale overdrachtssnelheid van gegevens: 2000 Mbit/s, Converter input interface: 10Base-T, 100Base-TX, 1000Base-T, Converter output interface: 1000Base-LX. Maximaal bereik: 40000 m, Golflengte: 1310 nm, Draad modus structuur: Single-mode. Kleur van het product: Zwart, Materiaal behuizing: Metaal. Vezel-optische connector: LC, Connectiviteitstechnologie: Bedraad. Ingangsspanning: 100 - 240 V, Stroom: 0.4 A, Spanning: 5 V



Netwerk		Poorten & interfaces	
Maximale overdrachtssnelheid van gegevens *	2000 Mbit/s	Aantal Ethernet LAN (RJ-45)-poorten	1
Converter input interface	10Base-T, 100Base-TX, 1000Base-T	Fibre channel-poorten	1
Converter output interface	1000Base-LX	Vezel-optische connector *	LC
Netwerkstandaard	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3z	Energie	
Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Ingangsspanning	100 - 240 V
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Stroom	0.4 A
Jumbo Frames ondersteuning	✓	Spanning	5 V
Jumbo frames	9000	Output current	2 A
Datastroombeheer	✗	Stroomverbruik (typisch)	4,6 W
Auto MDI/MDI-X	✓	Power over Ethernet (PoE)	✗
Auto-negotiation	✓	Gewicht en omvang	
Duplex systeem	Volledig, Half	Breedte	94 mm
Link Fault Pass-through (LFP)	✓	Diepte	79 mm
		Hoogte	26 mm
Prestatie		Eisen aan de omgeving	
Maximaal bereik *	40000 m	Bedrijfstemperatuur (T-T)	0 - 50 °C
Golflengte *	1310 nm	Temperatuur bij opslag	-10 - 70 °C
Golflengtemultiplexing (WDM)	✗	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Draad modus structuur	Single-mode	Inhoud van de verpakking	
Mean time between failures (MTBF)	50000 uur	Inclusief AC-adaptor	✓
		Gebruiksaanwijzing	✓
Kenmerken		Verpakking	
Intern *	✗	Breedte verpakking	133 mm
LED-indicatoren	✓	Diepte verpakking	280 mm
Kleur van het product	Zwart	Hoogte verpakking	66 mm
Materiaal behuizing	Metaal		

Poorten & interfaces		Verpakking	
Connectiviteitstechnologie	Bedraad	Gewicht verpakking	328 g
Certificaten			
Certificaten van naleving		CE, Federal Communications Commission (FCC), RoHS, Amerikaanse Federale wet inzake handelsovereenkomsten (TAA)	



0065030919876



065030919876

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.