

ZYXEL

Zyxel GS1200-8V3 Managed L2 Gigabit Ethernet (10/100/1000) Desktop Grijs



Merk : Zyxel

Artikelcode: GS1200-8V3-EU0101F

Productnaam : GS1200-8V3

Zyxel GS1200-8V3. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 8. Full duplex. MAC-adrestabel: 4000 entries, Switchingcapaciteit: 16 Gbit/s. Netwerkstandaard: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE.... Netstekker: DC-in ingang. Vormfactor: Desktop

Beheerfuncties		Multicast-functies	
Switch type *	Managed	Multicast-ondersteuning	✓
Switch-laag	L2	Aantal gefilterde multicast-groepen	128
Quality of Service (QoS)	✓	Design	
Web-gebaseerd management	✓	Rack-montage *	✗
Poorten & interfaces		Stapelbaar *	✗
Aantal basis-switching RJ-45 Ethernet-poorten *	8	Vormfactor	Desktop
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Kleur van het product	Grijs
Netstekker	DC-in ingang	LED-indicatoren	✓
Netwerk		Prestatie	
Netwerkstandaard *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Fanloos	✓
10G support *	✗	Mean time between failures (MTBF)	1266805 uur
Koperen ethernetbekabelingstechnologie	10BASE-T, 100BASE-T, 1000BASE-T	Energie	
Port mirroring	✓	Stroombron *	AC
Full duplex	✓	Vermogenstoever inclusief *	✓
Datastroombeheer	✓	AC-ingangsspanning	100 - 240 V
Broadcast stormbeheer	✓	AC-ingangsfrequentie	50/60 Hz
VLAN=ondersteuning	✓	Vermogensverbruik (max)	3,81 W
Virtuele LAN-functies	Port-based VLAN	Power over Ethernet (PoE)	
Data-uitwisseling		Power over Ethernet (PoE) *	✗
Switchingcapaciteit *	16 Gbit/s	Eisen aan de omgeving	
Verzending snelheid	11,9 Mpps	Bedrijfstemperatuur (T-T)	0 - 50 °C
MAC-adrestabel *	4000 entries	Temperatuur bij opslag	-40 - 70 °C
Jumbo Frames ondersteuning	✓	Relatieve vochtigheid in bedrijf (V-V)	10 - 95 procent
Jumbo frames	15	Luchtvochtigheid bij opslag	10 - 95 procent
Packet buffergeheugen	0,192 MB	Warmtedissipatie	13 BTU/h
Beveiliging		Gewicht en omvang	
DHCP-functies	DHCP client	Breedte	193 mm
IGMP snooping	✓	Diepte	85 mm
Wachtwoordbeveiliging	✓	Hoogte	26 mm
Algoritmen wachtrijplanning	Weighted Round Robin (WRR)	Gewicht	268 g
		Certificaten	
		Certificering	CE-LVD, BSMI CE, EAC, FCC, BSMI Class B



4718937649945

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.