



TP-Link Omada ES206X-M2 netwerk-switch Managed L2 2.5G Ethernet (100/1000/2500) Bureaublad-/wandmontage Zwart



Merk : TP-Link

Productfamilie: Omada

Artikelcode: ES206X-M2

Productnaam : ES206X-M2

TP-Link Omada ES206X-M2. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: 2.5G Ethernet (100/1000/2500), Aantal basis-switching RJ-45 Ethernet-poorten: 5. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 45 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3aq, IEEE.... Vormfactor: Bureaublad-/wandmontage

Beheerfuncties		Design	
Switch type *	Managed	Vormfactor	Bureaublad-/wandmontage
Switch-laag	L2	Kleur van het product	Zwart
Quality of Service (QoS)	✓	LED-indicatoren	✓
Poorten & interfaces		Prestatie	
Aantal basis-switching RJ-45 Ethernet-poorten *	5	Flash memory	64 MB
Type basis-switching RJ-45 Ethernet-poorten *	2.5G Ethernet (100/1000/2500)	Upgraden van firmware mogelijk	✓
Aantal moduleslots SPF+	1	Mean time between failures (MTBF)	1223587 uur
Netwerk		Energie	
Netwerkstandaard *	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3aq, IEEE 802.3x, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1ab	Stroombron *	AC
10G support *	✗	AC-ingangsspanning	100 - 240 V
Port mirroring	✓	Vermogensverbruik (max)	5,63 W
Datastroombeheer	✓	Power over Ethernet (PoE)	
Verbindingsaggregatie	✓	Power over Ethernet (PoE) *	✗
Broadcast stormbeheer	✓	Eisen aan de omgeving	
VLAN=ondersteuning	✓	Bedrijfstemperatuur (T-T)	-5 - 40 °C
Virtuele LAN-functies	MTU VLAN, Port-based VLAN	Temperatuur bij opslag	-40 - 70 °C
Data-uitwisseling		Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Switchingcapaciteit *	45 Gbit/s	Luchtvochtigheid bij opslag	5 - 90 procent
Verzending snelheid	33,48 Mpps	Warmtedissipatie	19,21 BTU/h
MAC-adrestabel *	16000 entries	Gewicht en omvang	
Store-and-forward	✓	Breedte	158 mm
Jumbo Frames ondersteuning	✓	Diepte	100,7 mm
Jumbo frames	10	Hoogte	25,4 mm
Packet buffergeheugen	0,64 MB	Gewicht	520 g
Beveiliging		Certificaten	
DHCP-functies	DHCP client	Certificering	CE, FCC, RoHS
IGMP snooping	✓		



1210002600729



0840460600323



840460600323

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.