

TP-Link ES206XPP-M2 netwerk-switch Managed L2 2.5G Ethernet (100/1000/2500) Power over Ethernet (PoE) Bureaublad-/wandmontage Zwart



Merk : TP-Link

Artikelcode: ES206XPP-M2

Productnaam : ES206XPP-M2

TP-Link ES206XPP-M2. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: 2.5G Ethernet (100/1000/2500), Aantal basis-switching RJ-45 Ethernet-poorten: 5. MAC-adrestabel: 16000 entries, Switchingcapaciteit: 45 Gbit/s. Netwerkstandaard: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3aq, IEEE.... Power over Ethernet (PoE). Vormfactor: Bureaublad-/wandmontage

Beheerfuncties		Design	
Switch type *	Managed	Kleur van het product	Zwart
Switch-laag	L2	LED-indicatoren	✓
Quality of Service (QoS)	✓	Prestatie	
Poorten & interfaces		Flash memory	64 MB
Aantal basis-switching RJ-45 Ethernet-poorten *	5	Upgraden van firmware mogelijk	✓
Type basis-switching RJ-45 Ethernet-poorten *	2.5G Ethernet (100/1000/2500)	Energie	
Aantal moduleslots SPF+	1	Stroombron *	AC/PoE
Netwerk		Vermogenstoevoer inclusief *	✓
Netwerkstandaard *	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3z, IEEE 802.3ae, IEEE 802.3aq, IEEE 802.3x, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1ab	AC-ingangsspanning	100 - 240 V
10G support *	✗	Power over Ethernet (PoE)	
Port mirroring	✓	Power over Ethernet (PoE) *	✓
Datastroombeheer	✓	Type Power over Ethernet (PoE) ondersteunt	PoE++ (4PPoE)
Verbindingsaggregatie	✓	Aantal Power over Ethernet 4PPoE (PoE++)-poorten	4
Broadcast stormbeheer	✓	Vermogen per poort Power over Ethernet (PoE)	90 W
VLAN=ondersteuning	✓	Totaal Power over Ethernet (PoE)-budget	120 W
Virtuele LAN-functies	MTU VLAN, Port-based VLAN	Eisen aan de omgeving	
Data-uitwisseling		Bedrijfstemperatuur (T-T)	-5 - 40 °C
Switchingcapaciteit *	45 Gbit/s	Temperatuur bij opslag	-40 - 70 °C
Verzending snelheid	33,48 Mpps	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
MAC-adrestabel *	16000 entries	Luchtvochtigheid bij opslag	5 - 90 procent
Store-and-forward	✓	Gewicht en omvang	
Jumbo Frames ondersteuning	✓	Breedte	209 mm
Jumbo frames	10	Diepte	126 mm
Packet buffergeheugen	0,64 MB	Hoogte	26 mm
Beveiliging		Certificaten	
DHCP-functies	DHCP client	Certificering	CE, FCC, RoHS
IGMP snooping	✓		
Design			
Vormfactor	Bureaublad-/wandmontage		



1210002600965



0840460600453



840460600453

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.