



Hyper 212 LED



Hyper 212 LED is equipped with PWM Fan with red LEDs and provides the best airflow and static pressure to take the heat away. And four direct contact heat pipes with funnel shaped aluminum fins provide the optimized CPU coolers for great performance. Moreover, the improved universal bracket designs ensure easy and worry free installation on all platforms.

Product Features

1. Four direct contact heat pipes for continuous contact between CPU and cooler
2. Upgradable to dual fans with quick snap fan bracket
3. Wide-range PWM fan with unique blade design and red LEDs
4. Versatile all-in-one mounting solution for Intel and AMD sockets
5. Optimized bracket design for easy installation

Package Information

EAN Code	4719512053379
UPC Code	884102029486
Carton Dimensions	475 x 330 x 255 mm
Unit / Carton	10 pcs
Carton / Pallet	48

Specification

CPU Socket	Intel LGA socket 2011-v3/2011/1151/1150/1155/1156/1366/775 AMD Socket AM3+ / AM3/AM2+/AM2 / FM2+/FM2 FM1
Dimensions	120 x 84 x 160mm (4.7 x 3.0 x 6.3 inch)
Heat Sink Dimensions	116 x 60 x 160mm (4.6 x 2.4 x 6.3 inch)
Heat Sink Material	4 Heat Pipes / Direct Contact / Aluminum Fins
Heat Sink Weight	468 g (1.03 lb)
Heat Pipe Dimensions	Ø6mm
Fan Dimensions	120 x 120 x 25mm (4.7 x 4.7 x 1inch)
Fan Speed	600 - 1600 RPM (PWM) ± 10%
Fan Air Flow	66.3 CFM ± 10%
Fan Air Pressure	1.7mm H ₂ O ± 10%
Fan MTTF	280,000 hours
Fan L-10 Life	40,000 hours
Noise Level	9 - 31 dBA
Bearing Type	Rifle Bearing
Connector	4 Pins
Rated Voltage	12 VDC
Rated Current	0.19 A
Power Consumption	2.28 W