

## PoE Injector

PoE feed-in adapter complies with standard IEEE 802.3af for supplying power to PoE-enabled IP devices using the network connection.

- The power requirement is automatically determined (max. 15.4 watts)
- Plug & play, no configuration necessary
- Compact design
- Designed for universal use



With the Auerswald PoE Injector, an IEEE 802.3af-compatible network device, such as a Wireless Access Point, IP telephone, or network camera, can be supplied with power directly over the network cable. This means it can also be connected using devices that are supplied by the network cable to a LAN switch port without a feed point.

Supplying power through the network connection reduces the number of cables and increases flexibility when choosing an installation location. There is no need for a separate wall-mounted power supply, only the network cable is required for connection and the device has to be located next to a mains socket.

---

## Technical Data

- **Operating voltage:** 100-240 V  $\pm$  10 %, 50 Hz
- **Output voltage:** 48 V DC, 350 mA
- **Standard:** IEEE 802.3af (class 0)
- **Ethernet ports:**
  - 1 x 10/100 Base-T (10/100MBit/s. RJ-45 Twisted-Pair)
  - 1 x 10/100 Base-T (10/100MBit/s. RJ-45 Twisted-Pair) with PoE
- **Case:** plastic
- **Colour:** Black
- **Dimensions (w x h x d):** 45 mm x 85 mm x 66 mm
- **Weight:** approx. 96 g
- **Security:** CE

## Scope of supply

- PoE feed-in adapter with standard IEEE 802.3af (class 0)

## Ordering information

- **Product designation:** PoE Injector
- **Part number:** 90075
- **EAN code:** 4019377900758

Copyright © 2016 Auerswald GmbH & Co. KG  
Version 1.0 – Subject to modifications