




LevelOne GNC-0122 netwerkkaart Intern Fiber

Merk : LevelOne

Artikelcode: GNC-0122

Productnaam : GNC-0122

LevelOne GNC-0122. Intern. Connectiviteitstechnologie: Bedraad, Hostinterface: PCI Express, Interface: Fiber. Kleur van het product: Aluminium



Poorten & interfaces		Eisen aan de omgeving	
Connectiviteitstechnologie *	Bedraad	Relatieve vochtigheid in bedrijf (V-V)	5 - 95 procent
Hostinterface *	PCI Express	Luchtvochtigheid bij opslag	5 - 95 procent
Interface *	Fiber		
Fibre channel-poorten	2		
Vezel-optische connector	SFP		
PCI versie	2.0		
Netwerk		Gewicht en omvang	
Netwerkstandaard *	IEEE 1588, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ad	Breedte	160 mm
Fiber ethernet cabling technologie	1000BASE-LX, 1000BASE-SX	Diepte	68 mm
Wake-on-LAN	✓	Hoogte	17 mm
Jumbo Frames ondersteuning	✓	Gewicht	83 g
Design		Verpakking	
Kleur van het product	Aluminium	Aantal	1
Intern *	✓	Breedte verpakking	145 mm
LED-indicatoren	Activiteit, Link	Diepte verpakking	220 mm
Land van herkomst	China	Hoogte verpakking	30 mm
		Gewicht verpakking	62 g
Minimale systeemeisen		Inhoud van de verpakking	
	Windows 2000, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	Montagebeugels meegeleverd	✓
Ondersteunt Windows		Gebruikershandleiding	✓
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS)	85176990
		Overige specificaties	
		Snelstartgids	✓
		Intel® Virtual Machine Device Queues (VMDq)	✓
Ondersteunde server operating systems	Windows Server 2003, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012 R2	Netvoeding	2,2 W

Eisen aan de omgeving

Bedrijfstemperatuur (T-T)	0 - 55 °C
Temperatuur bij opslag	-40 - 70 °C



4015867191071

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-SEP-2024. Prints or copies of Information are only valid on the printed Publication date