



ATEN 15A/10A 8-uitgangen 1U gemeten en geschakeld eco PDU

Merk : ATEN

Artikelcode: PE8108G-ATA-G



Productnaam : 15A/10A 8-uitgangen 1U gemeten en geschakeld eco PDU

15A/10A 8-uitgangen 1U gemeten en geschakeld eco PDU

ATEN 15A/10A 8-uitgangen 1U gemeten en geschakeld eco PDU:

- 8 uitgangen
- 15A (UL gereduceerd 12A) / 10A
- uitgangsstroommeting



De PE8108 eco PDU is een intelligente PDU die 8 wisselstroomuitgangen bevat en verkrijgbaar is in verschillende IEC- of NEMA-socketconfiguraties. Deze biedt veilig, gecentraliseerd, intelligent voedingsbeheer (in-, uitschakelen, in- en uitschakelen) van IT-apparatuur van gegevenscentra (servers, opslagsystemen, KVM-switches, netwerkapparaten, seriële gegevensapparaten, enz.), evenals de mogelijkheid om de gezondheidsomgeving van het centrum te bewaken via sensoren*.

1x PE8108 stroomverdelingseenheid

1x voedingskabel

1x rackmontagekit

1x software-cd

1x gebruikersinstructies

Design		Eisen aan de omgeving	
PDU types *	Gemeten, Geschakeld	Bedrijfstemperatuur (T-T)	0 - 50 °C
Rackcapaciteit *	1U	Temperatuur bij opslag	-20 - 60 °C
Montage	Horizontaal	Relatieve vochtigheid in bedrijf (V-V)	0 - 80 procent
Materiaal behuizing	Metaal	Gewicht en omvang	
Kleur van het product	Zwart	Breedte	220,4 mm
Poorten & interfaces		Diepte	432,4 mm
Aantal AC uitgangen *	8 AC-uitgang(en)	Hoogte	44 mm
Stekker	C20 stekker	Gewicht	3,22 kg
Stopcontacttypes *	C13 stekker	Inhoud van de verpakking	
Aantal Ethernet LAN (RJ-45)-poorten	1	Meegeleverde kabels	AC
Kenmerken		Rekbevestigingspakket	✓
LED-indicatoren	LAN, Link, Stroom, Status	Verpakking	
Snoerlengte	3 m	Gewicht verpakking	3,99 kg
Beheerfuncties		Breedte verpakking	116 mm
Monitoring	Stroom	Diepte verpakking	499 mm
Energie		Hoogte verpakking	324 mm
Nominale input voltage *	100 - 240 V	Logistieke gegevens	
AC-ingangsfrequentie	50 - 60 Hz	Netto gewicht kartonnen doos	9,66 kg
Stroom (max.) *	10 A	(Buitenste) hoofdverpakking breedte	388 mm
Netspanning, in bedrijf	100 - 240 V	(Buitenste) hoofdverpakking lengte	519 mm
Laad-capaciteit	2300 VA	(Buitenste) hoofdverpakking hoogte	348 mm
Maximale ingang stroom per fase	10 A	(Buitenste) hoofdverpakking brutogewicht	12,9 kg
Certificaten		Hoeveelheid per (buitenste) hoofdverpakking	3 stuk(s)
Certificaten van naleving	RoHS		
Certificering	CE, TUV-CB, CE-LVD, GOST,		



4710423777682

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-AUG-2025. Prints or copies of Information are only valid on the printed Publication date