

DIGITUS Professional CAT 6A Keystone Module, shielded, set= 24 pieces DN-93617-24 4016032365860



DIGITUS CAT 6A Keystone Jack, shielded
500 MHz acc.ISO/IEC 60603-7-51,11801 AMD2:2010-04, tool free connec., set 24 pcs

The shielded Keystone Module "DN-93617" from DIGITUS® provides best performance and link quality for your network. The compact design allows the installation of 24 pieces in a row of 483 mm (19") 1U Panels. It is conforming to Category 6A / 10GBase-T Channel, ANSI/EIA/TIA 568C.2.1:2002, ISO/IEC 11801:2002. Due to its compact size, this module suits into design compatible modular wall outlets (face plates).

- 1 This item is a set which consists of 24x DIGITUS® Keystone Module "DN-93617"
- 1 Material enclosure: Zinc diecast - Nickel plated
- 1 Material contacts: Phosphor bronze
- 1 Insertion force: max. 30N (acc. to IEC 60603-7-5)
- 1 Contacts coating: Nickel, gold plated 0.5 µ
- 1 Retention strength: 7.7 kg between jack and plug
- 1 Operating Temperature: -10 °C up to +60 °C (ISO/IEC 11801, ANSI/TIA 568 C.2)
- 1 Diameter Cu-Conductor: AWG (26/1 ... 22), stranded and solid
- 1 Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- 1 Tested with AWG 22 solid installation cable (DIGITUS® DK-1741-A-VH-X; AWG 22 CAT 7A installation cable)
- 1 CAT 6A transmission performance is compliance with the ANSI/TIA 568 C.2 standard
- 1 500 MHz acc. ISO/IEC 60603-7-51, 11801 AMD2:2010-04
- 1 Suitable for PoE/PoE+
- 1 RJ45 jack, for patch panel and modular wall outlet installation
- 1 Tool free cable installation via LSA stripes, color coded according to EIA/TIA 568 A & B
- 1 Cable entry: Rear side
- 1 Dimensions (HxWxD): 19.5 x 14.5 x 35.3 mm
- 1 Weight: 19 g



DIGITUS Professional CAT 6A Keystone Module, shielded, set= 24 pieces DN-93617-24 4016032365860



→ **Logistics**

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	864	18,40	23,40	53,50	31,30	39184,47
Packaging Unit Inside	24	0,51	7,50	16,50	6,50	804,38
Packaging Unit Single	1	0,02	3,10	1,50	2,10	9,77
Net single without Packaging	1	0,00	3,10	1,50	2,10	9,77

→ **Packaging type**

