

# Rittal – The System.

Faster – better – everywhere.

## **Socket strips in an aluminium duct – DK 7240.210**

Date : Jul 7, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Socket strips in an aluminium duct – DK 7240.210

created : 07.07.2014 on [www.rittal.com/com-en](http://www.rittal.com/com-en)



## Product description

### Benefits:

- Practical, universal fastening
- Providing flexibility and saving on warehousing.
- In the the 482.6 mm (19") section there is adequate space to route the infeed between the socket strip and the mounting angle without kinks
- The arrangement of the earthing-pin sockets at a 45° angle allows unrestricted use of angular connectors.

### Material:

- Aluminium section, natural anodised
- Socket inserts: Polycarbonate

### Standards:

- DIN 49 440-1

### Supply includes:

- Socket strip
- Two mounting brackets
- Assembly parts

### Packs of:

- 1 pc(s).

### EAN:

- 4028177221161




### Customs tariff number:

- 85369085

## Product features

### Design:

- Without switch

<b>Dimensions:</b>	<ul style="list-style-type: none"> <li>• Height: 44 mm</li> <li>• Depth: 44 mm</li> </ul>
<b>Installation options:</b>	<ul style="list-style-type: none"> <li>• Components with a 25 mm pitch pattern</li> <li>• Enclosure frame</li> <li>• IT wall-mounted distributor, at the rear, horizontal (adequate width provided)</li> <li>• 482.6 mm (19") level</li> </ul>
<b>Length:</b>	<ul style="list-style-type: none"> <li>• 482.6 mm</li> </ul>
<b>Mounting dimensions:</b>	<ul style="list-style-type: none"> <li>• 452.5 mm</li> <li>• Tolerance: 25 mm</li> </ul>
<b>Rated voltage:</b>	<ul style="list-style-type: none"> <li>• 250 V AC</li> </ul>
<b>Rated current (max.):</b>	<ul style="list-style-type: none"> <li>• 16 A</li> </ul>
<b>Equipment (electrical):</b>	<ul style="list-style-type: none"> <li>• Number of sockets: 7</li> <li>• Jack/socket (type): D, earthing-pin (type F, CEE7/3)</li> <li>• Length of connection cable: 2 m</li> </ul>
<b>Connection cable (type):</b>	<ul style="list-style-type: none"> <li>• H05VV-F3G1.5</li> </ul>
<b>Weight:</b>	<ul style="list-style-type: none"> <li>• 0.88 kg</li> </ul>
<b>Approvals</b>	
<b>Approvals:</b>	<ul style="list-style-type: none"> <li>•  <a href="#">VDE (DE)</a></li> </ul>
<b>Declarations:</b>	<ul style="list-style-type: none"> <li>•  <a href="#">Declaration of conformity (DE)</a></li> </ul>
<b>Downloads</b>	
<b>Data sheets:</b>	<ul style="list-style-type: none"> <li>•  <a href="#">Technical details (EN)</a></li> </ul>

# Rittal – The System.

---

**Faster – better – everywhere.**

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG  
Postfach 1662 · D-35726 Herborn  
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319  
E-Mail: [info@rittal.com](mailto:info@rittal.com) · [www.rittal.com](http://www.rittal.com)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

