

StarTech.com 4-poorts PCI Express USB 3.0 kaart 2 extern, 2 intern SATA-voeding

Merk : StarTech.com

Artikelcode: PEXUSB3S2EI

Productnaam : 4-poorts PCI Express USB 3.0 kaart 2 extern, 2 intern SATA-voeding




StarTech.com 4 Port PCI Express USB 3.0 Kaart - 5Gbps - 2 Extern & 2 Intern - SATA Voeding - UASP Support - 2 Moederbord Headers (PEXUSB3S2EI)

[StarTech.com 4-poorts PCI Express USB 3.0 kaart 2 extern, 2 intern SATA-voeding:](#)

Voeg 2 interne en 2 externe SuperSpeed USB 3.0 (USB 3.2 Gen 1) poorten toe aan uw PC via een PCIe slot

The StarTech.com Advantage

StarTech.com 4-poorts PCI Express USB 3.0 kaart 2 extern, 2 intern SATA-voeding. Hostinterface: PCIe, Output interface: SATA, USB 3.2 Gen 1 (3.1 Gen 1), Uitbreidingskaart vormfactor: Volledige hoogte / Laag profiel. Kleur van het product: Metallic, Rood, Maximum kabellengte: 3 m, Mean time between failures (MTBF): 1920042 uur. Chipset: Renesas / NEC - μ PD720201, Data transfer snelheid (max): 5 Gbit/s. Ondersteunt Windows: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Ondersteunde server operating systems: Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows.... Breedte: 18 mm, Diepte: 92 mm, Hoogte: 120 mm



Poorten & interfaces		Technische details	
Hostinterface *	PCIe	Certificaten van naleving	CE, RoHS
Output interface *	SATA, USB 3.2 Gen 1 (3.1 Gen 1)	Gewicht en omvang	
Uitbreidingskaart vormfactor	Volledige hoogte / Laag profiel	Breedte	18 mm
Uitbreidingskaartstandaard	PCI 2.0	Diepte	92 mm
Aantal poorten USB 3.2 Gen 1 (3.1 Gen 1) Type A	2	Hoogte	120 mm
Aantal Internal SATA ports	1	Gewicht	53 g
Design		Verpakking	
Intern *	✓	Montagebeugels meegeleverd	✓
Kleur van het product	Metallic, Rood	Meegeleverde drivers	✓
Maximum kabellengte	3 m	Gebbruikershandleiding	✓
Mean time between failures (MTBF)	1920042 uur	Breedte verpakking	174 mm
Kenmerken		Diepte verpakking	143 mm
Chipset	Renesas / NEC - μ PD720201	Hoogte verpakking	33 mm
Data transfer snelheid (max)	5 Gbit/s	Gewicht verpakking	143 g
UASP-ondersteuning	✓	Logistieke gegevens	
Eisen aan de omgeving		Code geharmoniseerd systeem (HS)	84733020
Bedrijfstemperatuur (T-T)	5 - 50 °C	Hoeveelheid per (buitenste) hoofdverpakking	60 stuk(s)
Temperatuur bij opslag	-25 - 70 °C	(Buitenste) hoofdverpakking breedte	383 mm
Relatieve vochtigheid in bedrijf (V-V)	20 - 80 procent	(Buitenste) hoofdverpakking lengte	495 mm
		(Buitenste) hoofdverpakking hoogte	316 mm
		Overige specificaties	
		Maximale afstand	3 m

Minimale systeemeisen

Ondersteunt Windows	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IoT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Ondersteunde server operating systems	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019



0065030860338



065030860338



0723856593525



723856593525

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.