



APC Rack PDU AP7921B, Switched, 0U/1U, 16A, 230V,(8x) C13, C20 stekker

Merk : APC

Artikelcode: AP7921B

Productnaam : APC Rack PDU AP7921B, Switched, 0U/1U, 16A, 230V,(8x) C13, C20 stekker




APC Rack PDU AP7921B, Switched, 0U/1U, 16A, 230V,(8x) C13, C20 stekker
APC Rack PDU AP7921B, Switched, 0U/1U, 16A, 230V,(8x) C13, C20 stekker. PDU types: Gemeten, Geschakeld, Rackcapaciteit: 0U/1U, Montage: Horizontaal/Verticaal. Aantal AC uitgangen: 8 AC-uitgang(en), Stopcontacttypes: C13 stekker, Stekker: C20 stekker. Snoerlengte: 2,5 m. Monitoring: Stroom, Stroom, Spanning, Outlet controle: Lockout, Recyclen, Uitschakelen, Inschakelen. Nominale input voltage: 200-230 V, Stroom (max.): 16 A, AC-ingangsfrequentie: 50 - 60 Hz

Design		Certificaten	
PDU types *	Gemeten, Geschakeld	Certificaten van naleving	RoHS
Rackcapaciteit *	0U/1U		cUL Listed, CE, CSA, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IRAM, MIC, UL 60950, UL Listed, VDE, VCCI, REACH
Montage	Horizontaal/Verticaal	Certificering	
Kleur van het product	Zwart		
Poorten & interfaces		Eisen aan de omgeving	
Aantal AC uitgangen *	8 AC-uitgang(en)	Bedrijfstemperatuur (T-T)	0 - 45 °C
Stekker	C20 stekker	Temperatuur bij opslag	-25 - 65 °C
Stopcontacttypes *	C13 stekker	Relatieve vochtigheid in bedrijf (V-V)	0 - 95 procent
Input-connectietype	IEC-320 C20	Luchtvochtigheid bij opslag	0 - 95 procent
Kenmerken		Hoogte, in bedrijf	0 - 3000 m
Snoerlengte	2,5 m	Hoogte bij opslag	1 - 15000 m
Beheerfuncties		Gewicht en omvang	
Monitoring	Stroom, Stroom, Spanning	Breedte	445 mm
Outlet controle	Lockout, Recyclen, Uitschakelen, Inschakelen	Diepte	108 mm
Energie		Hoogte	44 mm
Nominale input voltage *	200-230 V	Gewicht	2,27 kg
AC-ingangsfrequentie	50 - 60 Hz	Verpakking	
Stroom (max.) *	16 A	Gewicht verpakking	3,45 kg
Netspanning, in bedrijf	208-230 V	Breedte verpakking	470 mm
Laad-capaciteit	3680 VA	Diepte verpakking	343 mm
Maximale ingang stroom per fase	16 A	Hoogte verpakking	70 mm
Maximum totaalstroomverbruik per fase	16 A	Logistieke gegevens	
Maximaal vermogen	3680 W	Totale Koolstofvoetafdruk (kg of CO2e)	915,89



0731304331629



731304331629

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.