

# Intellinet 561334 netwerk-switch Managed L2 Gigabit Ethernet (10/100/1000) Zwart



**Merk :** Intellinet

**Artikelcode:** 561334

**Productnaam :** 561334

Intellinet 561334. Switch type: Managed, Switch-laag: L2. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 48. Full duplex. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 104 Gbit/s. Netwerkstandaard: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE...

| Beheerfuncties                                  |  | Data-uitwisseling                         |                                    |
|---|--|---|------------------------------------|
| Switch type *                                   | Managed  | Packet forwarding rate (10 Mbps)          | 14880 pps                          |
| Switch-laag                                     | L2   | Packet buffergeheugen                     | 1,5 MB                             |
| Quality of Service (QoS)                        | ✓  | <b>Beveiliging</b>                        |                                    |
| Web-gebaseerd management                        | ✓  | IGMP snooping                             | ✓                                  |
| <b>Poorten &amp; interfaces</b>                 |  | Ondersteunde beveiligingsalgoritmen       | SNMP, SSH-2                        |
| Aantal basis-switching RJ-45 Ethernet-poorten * | 48   | <b>Multicast-functies</b>                 |                                    |
| Type basis-switching RJ-45 Ethernet-poorten *   | Gigabit Ethernet (10/100/1000)   | Multicast-ondersteuning                   | ✓                                  |
| Aantal moduleslots SPF                          | 4  | <b>Protocollen</b>                        |                                    |
| Vezel-optische connector                        | MiniGBIC   | Ondersteunde netwerkprotocollen           | IPv4, IPv6                         |
| <b>Netwerk</b>                                  |  | <b>Design</b>                             |                                    |
| Netwerkstandaard *                              | IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | Kleur van het product                     | Zwart                              |
| 10G support *                                   | ✗  | Materiaal behuizing                       | Metaal                             |
| Koperen ethernetbekabelingstechnologie          | 10BASE-T, 100BASE-TX, 1000BASE-T   | LED-indicatoren                           | Activiteit, Link, Stroom, Snelheid |
| Ondersteundende kabel types                     | Cat3, Cat4, Cat5, Cat5e  | Certificering                             | FCC A, CE                          |
| Port mirroring                                  | ✓  | <b>Energie</b>                            |                                    |
| Full duplex                                     | ✓  | AC-ingangsspanning                        | 100 - 240 V                        |
| Datastroombeheer                                | ✓  | AC-ingangsfrequentie                      | 50 - 60 Hz                         |
| Verbindingsaggregatie                           | ✓  | Vermogensverbruik (max)                   | 36 W                               |
| Broadcast stormbeheer                           | ✓  | <b>Power over Ethernet (PoE)</b>          |                                    |
| Rate limiting                                   | ✓  | Power over Ethernet (PoE) *               | ✗                                  |
| Auto MDI/MDI-X                                  | ✓  | <b>Eisen aan de omgeving</b>              |                                    |
| Spanning tree protocol                          | ✓  | Bedrijfstemperatuur (T-T)                 | 0 - 40 °C                          |
| Auto-negotiation                                | ✓  | Temperatuur bij opslag                    | -20 - 70 °C                        |
| VLAN=ondersteuning                              | ✓  | Relatieve vochtigheid in bedrijf (V-V)    | 10 - 90 procent                    |
| Virtuele LAN-functies                           | Tagged VLAN, Port-based VLAN   | <b>Gewicht en omvang</b>                  |                                    |
| <b>Data-uitwisseling</b>                        |  | Breedte                                   | 440 mm                             |
| Switchingcapaciteit *                           | 104 Gbit/s   | Diepte                                    | 335 mm                             |
| MAC-adrestabel *                                | 8000 entries   | Hoogte                                    | 44 mm                              |
| Store-and-forward                               | ✓  | Gewicht                                   | 4,2 kg                             |
| Jumbo Frames ondersteuning                      | ✓  | <b>Verpakking</b>                         |                                    |
| Jumbo frames                                    | 9000   | Meegeleverde kabels                       | AC                                 |
| Packet forwarding rate (1 Gbps)                 | 1488000 pps  | Gebruikershandleiding                     | ✓                                  |
| Packet forwarding rate (100 Mbps)               | 148800 pps   | Rekbevestigingspakket                     | ✓                                  |
| <b>Logistieke gegevens</b>                      |  | Code geharmoniseerd systeem (HS) 85176990 |                                    |



0766623561334



766623561334

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-MAR-2024. Prints or copies of Information are only valid on the printed Publication date