

TP-Link RE450 Netwerkzender & -ontvanger Wit 10, 100, 1000 Mbit/s

Merk : TP-Link

Artikelcode: RE450 (DE)

Productnaam : RE450

TP-Link RE450. Soort: Netwerkzender & -ontvanger, Overdrachtssnelheid: 1300 Mbit/s, Ethernet LAN, data-overdrachtssnelheden: 10,100,1000 Mbit/s. Soort antenne: Extern, Zendvermogen (CE): 2.4 GHz ≤20dBm, 5 GHz ≤23dBm. Bekabelingstechnologie: 10/100/1000Base-T(X), Netwerkstandaard: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3ab,...., Wi-Fi-standaarden: 802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n). Kleur van het product: Wit, Aantal per verpakking: 1 stuk(s). AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50/60 Hz, Vermogensverbruik (max): 9 W



Prestatie		Design	
Soort *	Netwerkzender & -ontvanger	Aantal per verpakking	1 stuk(s)
Overdrachtssnelheid	1300 Mbit/s	Aan/uitschakelaar	✓
Ethernet LAN, data-overdrachtssnelheden	10,100,1000 Mbit/s	Reset button	✓
WPS Push Button Security	✓	Energie	
Ondersteunt Windows	✓	AC-ingangsspanning	100 - 240 V
Mac-compatibiliteit	✓	AC-ingangsfrequentie	50/60 Hz
Ondersteunt Mac-besturingssysteem	✓	Vermogensverbruik (max)	9 W
Ondersteunt Linux	✓	Eisen aan de omgeving	
Antenne		Bedrijfstemperatuur (T-T)	0 - 30 °C
Antennas quantity	3	Temperatuur bij opslag	-40 - 70 °C
Soort antenne	Extern	Relatieve vochtigheid in bedrijf (V-V)	10 - 90 procent
Zendvermogen (CE)	2.4 GHz ≤20dBm, 5 GHz ≤23dBm	Luchtvochtigheid bij opslag	5 - 90 procent
Netwerk		Gewicht en omvang	
Bekabelingstechnologie	10/100/1000Base-T(X)	Breedte	163 mm
Netwerkstandaard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u	Diepte	67,4 mm
Wifi	✓	Hoogte	66,5 mm
Wi-Fi-standaarden	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Technische details	
Draadloos LAN data-overdrachtssnelheid (max)	1300 Mbit/s	Duurzaamheidscertificaten	RoHS
Wifi-band	Dual-band (2.4 GHz / 5 GHz)	Inhoud van de verpakking	
Ondersteunde beveiligingsalgoritmen	64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK, WPS	Meegeleverde kabels	LAN (RJ-45)
Poorten & interfaces		Snelstartgids	✓
Aantal Ethernet LAN (RJ-45)-poorten	1	Verpakking	
		Breedte verpakking	202 mm
		Diepte verpakking	125 mm
		Hoogte verpakking	86 mm

Design

Kleur van het product Wit
LED-indicatoren ✓

Verpakking

Gewicht verpakking 350 g

Logistieke gegevens

Code geharmoniseerd systeem (HS) 85176990



6935364082598

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 12-MAR-2024. Prints or copies of Information are only valid on the printed Publication date