



Delock HDMI Audio Extractor 4K 60 Hz compact

Description

This adapter by Delock can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.



Specification

- Connectors:
 - Input:
 - 1 x HDMI-A 19 pin male
 - 1 x USB Type Micro-B female (5 V power supply)
 - Output:
 - 1 x HDMI-A 19 pin female
 - 1 x 3.5 mm 3 pin stereo jack female (audio)
 - 1 x TOSLINK female S/PDIF
- High Speed HDMI, 3D and HDCP 1.4 / HDCP 2.2
- Automatic switching to stereo (2.0) when using the stereo jack and automatic muting of the digital output
- Resolution up to 3840 x 2160 @ 60 Hz
- Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gb/s
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- HDMI audio routed to the output (pass-through)
- Power consumption: max. 2 W

System requirements

- A free HDMI-A female
- A free USB Type-A female port

Package content

- HDMI Audio Extractor
- USB Type-A to Type Micro-B cable, length ca. 30 cm
- User manual

Item no. 63276

EAN: 4043619632763


Country of origin: China

Package: Retail Box





Images





General	
Specification:	DTS Audio High Speed HDMI Dolby Digital HDCP 1.4 HDCP 2.2 LPCM
Interface	
Output:	1 x 3.5 mm 3 pin stereo jack female 1 x HDMI-A 19 pin female 1 x TOSLINK female
Input:	1 x HDMI-A 19 pin male 1 x USB 2.0 type Micro-B female
Technical characteristics	
Maximum screen resolution:	3840 x 2160 @ 60 Hz
Video bandwidth:	600 MHz / 6 Gbps
Physical characteristics	
Housing colour:	black
Housing material:	Plastic