# Delock Adapter USB Type-C™ male > HDMI female (DP Alt

## Description

Mode) 4K 30 Hz

This Delock adapter is suitable for the connection of an HDMI monitor to a computer with USB-C<sup>™</sup> interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like Macbook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt<sup>™</sup> 3 interface.

### Specification

#### · Connectors:

- 1 x USB Type-C<sup>™</sup> male >
- 1 x HDMI-A 19 pin female
- Chipset: Realtek RTD2171U
- DisplayPort 1.4 and High Speed HDMI with Ethernet (HEC) specification
- Resolution up to 1920 x 1200 @ 60 Hz / 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- USB bus powered
- Plug & Play
- · Gold-plated connectors
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- Colour: black

#### System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, Linux ex Kernel 4.3, Mac ex OS 10.12, Android ex 6.0
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt<sup>™</sup> 3 port

#### Package content

USB-C<sup>™</sup> to HDMI adapter

### Images







ltem no. 62999

EAN: 4043619629992

Country of origin: China

Package: Retail Box



© 2018 by Delock . All names and symbols mentioned here are property of the respective producer. Printing errors, changes and errors excepted.





# \_\_\_\_\_





General	
Function:	Plug & Play
Specification:	High Speed HDMI with Ethernet
	HDCP 1.4
	HDCP 2.2
	DisplayPort 1.4
Supported operating system:	Android ex 6.0
Supported operating system.	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Windows 10 Mobile
	ex Linux Kernel 4.3
	ex Mac OS 10.12
Interface	
Output:	1 x HDMI-A 19 pin female
Input:	1 x USB Type-C™ male
Technical characteristics	
Chipset:	Realtek RTD2171U
Maximum screen resolution:	3840 x 2160 @ 30 Hz
	1920 x 1200 @ 60 Hz
Signal transmission:	video
	audio
Physical characteristics	
Ferrite core:	1 x
Cable length:	20 cm
Connector finishing:	gold-plated