# DATASHEET



# Delock Adapter USB Type-C<sup>™</sup> male > DisplayPort female (DP Alt Mode) 4K 60 Hz

#### Description

This adapter by Delock is suitable for the connection of a DisplayPort monitor to a computer with USB-C<sup>™</sup> interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt<sup>™</sup> 3 interface.



ltem no. 63312

EAN: 4043619633128

Country of origin: China

Package: Retail Box



#### Specification

#### Connectors:

- 1 x USB Type-C<sup>™</sup> male >
- 1 x DisplayPort 20 pin female
- Chipset: VIA VL100
- DisplayPort 1.2 specification
- Resolution up to 4096 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- · Transmission of audio and video signals
- · USB bus powered
- · Plug & Play
- Gold-plated connectors
- 1 x ferrite core
- · Cable length without connectors: ca. 20 cm
- Colour: black

# System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Windows 10 Mobile, Chrome OS, Linux ex Kernel 4.3, Mac ex OS 10.12, Android ex 6.0
- PC or laptop with a free USB Type-C<sup>™</sup> port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt<sup>™</sup> 3 port

# Package content

USB-C<sup>™</sup> to DisplayPort adapter

### Images









General	
Function:	Plug & Play
Specification:	DisplayPort 1.2
Supported operating system:	Android ex 6.0
	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Windows 10 Mobile
	ex Linux Kernel 4.3
	ex Mac OS 10.12
Interface	
Output:	1 x DisplayPort 20 pin female
Input:	1 x USB Type-C™ male
Technical characteristics	
Chipset:	VIA VL100
Maximum screen resolution:	4096 x 2160 @ 60 Hz
Signal transmission:	video
	audio
Physical characteristics	audio
Physical characteristics Ferrite core:	audio 1 x
Ferrite core:	1 x