

ASUS WS X299 SAGE/10G Intel® X299 LGA 2066 (Socket R4) SSI CEB

Merk : ASUS

Artikelcode: 90SW00H0-M0EAY0

Productnaam : WS X299 SAGE/10G

ASUS WS X299 SAGE/10G. Processorfabrikant: Intel, Processor socket: LGA 2066 (Socket R4), Supported processor sockets: LGA 2066. Ondersteunde geheugen types: DDR4-SDRAM, Maximum intern geheugen: 512 GB, Geheugen kanaal: Vierkanaals. Ondersteunde opslagstationinterfaces: SATA III, Soorten RAID: 0, 1, 5, 10. Ondersteuning voor parallel processing: 4-Way CrossFireX, 4-Way SLI. Ethernet interface type: 10 Gigabit Ethernet, LAN controller: Intel® X550-AT2



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	1
Processor socket *	LGA 2066 (Socket R4)	USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1
Supported processor sockets	LGA 2066	Ethernet LAN (RJ-45) ports *	2
Memory		Network	
Supported memory types *	DDR4-SDRAM	Ethernet LAN	✓
Number of memory slots *	8	Ethernet interface type	10 Gigabit Ethernet
Memory channels	Quad-channel	LAN controller	Intel® X550-AT2
ECC compatibility	ECC & Non-ECC	Wi-Fi *	✗
Supported memory clock speeds	2133,2400,2666 MHz	Features	
Maximum internal memory *	512 GB	Motherboard chipset *	Intel® X299
Storage controllers		Audio chip	Realtek ALC S1220A
Supported storage drive interfaces *	SATA III	Audio output channels *	7.1 channels
RAID support	✓	Product colour	Black
RAID levels	0, 1, 5, 10	Component for *	Workstation
Graphics		Motherboard form factor *	SSI CEB
Parallel processing technology support *	4-Way CrossFireX, 4-Way SLI	Motherboard chipset family *	Intel
Internal I/O		Certification	CE
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Expansion slots	
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	1	PCI Express x16 (Gen 3.x) slots	7
Number of SATA III connectors *	8	Number of M.2 (M) slots	2
ATX Power connector (24-pin)	✓	BIOS	
Number of EATX power connectors	1	BIOS type *	UEFI
CPU fan connector	✓	Clear CMOS button	✓
Number of chassis fan connectors	2	Operational conditions	
		Storage temperature (T-T)	-40 - 70 °C

Internal I/O		Operational conditions	
EPS power connector (8-pin)	✓	Operating temperature (T-T)	10 - 35 °C
Number of COM connectors	1	Operating relative humidity (H-H)	20 - 90%
TPM connector	✓	Logistics data	
Rear panel I/O ports		Harmonized System (HS) code	84733020
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	Weight & dimensions	
		Width	305 mm
		Depth	267 mm
		Height	287 mm
		Packaging content	
		Cables included	SATA
		Other features	
		Weight	2.2 kg



0753459461204



753459461204



4712900952001

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.