



# LevelOne USB-0402 netwerkkaart Ethernet 1000 Mbit/s

Merk : LevelOne

Artikelcode: USB-0402

Productnaam : USB-0402

LevelOne USB-0402. Connectiviteitstechnologie: Bedraad, Hostinterface: USB Type-C, Interface: Ethernet. Maximale overdrachtssnelheid van gegevens: 1000 Mbit/s. Stroomvoorziening via USB. Kleur van het product: Zilver, Wit



| Poorten & interfaces                        |                                                                  | Minimale systeemeisen                  |                                                                                                                                                                                 |
|---------------------------------------------|------------------------------------------------------------------|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connectiviteitstechnologie *                | Bedraad                                                          | Ondersteunt Mac-besturingssysteem      | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks |
| Hostinterface *                             | USB Type-C                                                       |                                        |                                                                                                                                                                                 |
| Interface *                                 | Ethernet                                                         |                                        |                                                                                                                                                                                 |
| Aantal Ethernet LAN (RJ-45)-poorten         | 1                                                                |                                        |                                                                                                                                                                                 |
| USB-versie                                  | 3.2 Gen 2 (3.1 Gen 2)                                            |                                        |                                                                                                                                                                                 |
| Netwerk                                     |                                                                  | Eisen aan de omgeving                  |                                                                                                                                                                                 |
| Maximale overdrachtssnelheid van gegevens * | 1000 Mbit/s                                                      | Bedrijfstemperatuur (T-T)              | 10 - 40 °C                                                                                                                                                                      |
| Netwerkstandaard *                          | IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x | Temperatuur bij opslag                 | 10 - 70 °C                                                                                                                                                                      |
| Ethernet LAN                                | ✓                                                                | Relatieve vochtigheid in bedrijf (V-V) | 0 - 85 procent                                                                                                                                                                  |
| Ethernet interface type                     | Gigabit Ethernet                                                 | Luchtvochtigheid bij opslag            | 0 - 85 procent                                                                                                                                                                  |
| Ethernet LAN, data-overdrachtsnelheden      | 10,100,1000 Mbit/s                                               | Gewicht en omvang                      |                                                                                                                                                                                 |
| Bekabelingstechnologie                      | 10/100/1000BaseT(X)                                              | Breedte                                | 28,5 mm                                                                                                                                                                         |
| Koperen ethernetbekabelingstechnologie      | 10BASE-T, 100BASE-TX, 1000BASE-T                                 | Diepte                                 | 17,5 mm                                                                                                                                                                         |
| Wake-on-LAN                                 | ✓                                                                | Hoogte                                 | 217 mm                                                                                                                                                                          |
| Auto MDIX IEEE                              | ✓                                                                | Gewicht                                | 26 g                                                                                                                                                                            |
| Full duplex                                 | ✓                                                                | Verpakking                             |                                                                                                                                                                                 |
| Jumbo Frames ondersteuning                  | ✓                                                                | Type verpakking                        | Doos                                                                                                                                                                            |
| Jumbo frames                                | 9000                                                             | Breedte verpakking                     | 90 mm                                                                                                                                                                           |
| Ondersteunde netwerkprotocollen             | IPv4/IPv6                                                        | Diepte verpakking                      | 26 mm                                                                                                                                                                           |
| Design                                      |                                                                  | Hoogte verpakking                      | 212 mm                                                                                                                                                                          |
| Kleur van het product                       | Zilver, Wit                                                      | Gewicht verpakking                     | 33 g                                                                                                                                                                            |
| Intern *                                    | ✗                                                                | Inhoud van de verpakking               |                                                                                                                                                                                 |
| Land van herkomst                           | China                                                            | Snelle installatiehandleiding          | ✓                                                                                                                                                                               |
| Certificering                               | CE                                                               | Technische details                     |                                                                                                                                                                                 |
| Energie                                     |                                                                  | Certificaten van naleving              | RoHS                                                                                                                                                                            |
| Stroom                                      | 3 A                                                              | Logistieke gegevens                    |                                                                                                                                                                                 |
| Spanning                                    | 5 V                                                              | (Buitenste) hoofdverpakking breedte    | 390 mm                                                                                                                                                                          |
| Stroomverbruik (typisch)                    | 2 W                                                              | (Buitenste) hoofdverpakking lengte     | 280 mm                                                                                                                                                                          |
| Stroomvoorziening via USB                   | ✓                                                                | (Buitenste) hoofdverpakking hoogte     | 540 mm                                                                                                                                                                          |

| Minimale systeemeisen |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Logistieke gegevens                         |             |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|-------------|
| Ondersteunt Windows   | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64 | (Buitenste) hoofdverpakking brutogewicht    | 7,7 kg      |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Hoeveelheid per (buitenste) hoofdverpakking | 120 stuk(s) |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Overige specificaties                       |             |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Datastroombeheer                            | ✓           |



4015867202371



4015867227220



0846359047873



846359047873

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.