



TP-Link RE335 Netwerkrepeater 867 Mbit/s Wit

Merk : TP-Link

Artikelcode: RE335(DE)

Productnaam : RE335

TP-Link RE335. Maximale overdrachtsnelheid van gegevens: 867 Mbit/s. Antenne-ontwerp: Intern. Wifi-band: Dual-band (2.4 GHz / 5 GHz), Wifi-standaard: Wi-Fi 5 (802.11ac), WLAN gegevensoverdrachtsnelheid (max): 867 Mbit/s. Interfacetype Ethernet LAN: Fast Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100 Mbit/s, Netwerkstandaard: IEEE 802.3, IEEE 802.3u. Connectiviteitstechnologie: Bedraad en draadloos



Data-uitwisseling		Beveiliging	
Maximale overdrachtsnelheid van gegevens *	867 Mbit/s	WPS Push Button Security	✓
Antenne		Kenmerken	
Antenne-ontwerp	Intern	Type product *	Netwerkrepeater
Antennas quantity	2	Kleur van het product	Wit
Draadloos LAN		LED-indicatoren	✓
Wifi	✓	Power LED	✓
Wifi-band	Dual-band (2.4 GHz / 5 GHz)	Reset button	✓
Wifi-standaard	Wi-Fi 5 (802.11ac)	Minimale systeemeisen	
WLAN gegevensoverdrachtsnelheid (max)	867 Mbit/s	Compatibele besturingssystemen	Microsoft Windows 98SE, NT, 2000, XP, Vista, Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX, Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Signaalsterkte	30 dBm	Energie	
Gevoeligheid ontvanger	5 GHz: 11a 6Mbps: -94dBm, 11a 54Mbps: -77dBm 11ac HT20 MCS0: -94dBm, 11ac HT20 MCS8: -71dBm 11ac HT40 MCS0: -92dBm, 11ac HT40 MCS9: -66dBm 11ac HT80 MCS0: -87dBm, 11ac HT80 MCS9: -62dBm 2.4 GHz: 11g 54Mbps: -78dBm, 11n HT20 MCS7: -76dBm 11n HT40 MCS7: -74dBm	Type stroombron	AC
Netwerk		AC-ingangsspanning	100 - 240 V
Ethernet LAN	✓	AC-ingangsfrequentie	50/60 Hz
Interfacetype Ethernet LAN	Fast Ethernet	Stroomverbruik (typisch)	9,5 W
Ethernet LAN, data-overdrachtsnelheden	10,100 Mbit/s	Vermogensverbruik (max)	9,5 W
Netwerkstandaard	IEEE 802.3, IEEE 802.3u	Certificaten	
Poorten & interfaces		Certificering	FCC, RoHS
Connectiviteitstechnologie	Bedraad en draadloos	Gewicht en omvang	
Aantal Ethernet LAN (RJ-45)-poorten	1	Breedte	69,5 mm
		Diepte	35 mm
		Hoogte	124,1 mm
		Inhoud van de verpakking	
		Snelle installatiehandleiding	✓

Beveiliging		Technische details	
Ondersteunde beveiligingsalgoritmen	64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK	Certificaten van naleving	CE, RoHS
Verpakking		Type verpakking	Doos
		Aantal per verpakking	1 stuk(s)



4897098681992

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-SEP-2024. Prints or copies of Information are only valid on the printed Publication date