

TS-351-2G	
CPU	Intel® Celeron® J1800 dual core 2.41 GHz processor, up to 2.58 GHz
System Memory	2 GB DDR3L (1 x 2 GB)
Maximum Memory	8 GB (2 x 4 GB)
Memory Slot	2 x SODIMM slot
Flash Memory	512 MB NAND Flash
Drive Bay	Hot-swappable 3 x 3.5"/2.5" SATA HDDs/SSDs Note: 1. HDD 1~2 supports SATA 3Gb/s, HDD 3 supports SATA 6Gb/s 2. 2.5-inch HDD/SSD drive tray bases can be purchased from QNAP Online Shop
M.2 SSD Slot	2 x M.2 PCIe (Gen2 x1, up to 500 MB/s) NVMe 2280 slots Note: 1. The M.2 SSD is not included as standard. 2. M.2 SSD operations can easily generate excessive heat. It is recommended to install a heatsink (from QNAP or a third-party provider) on the M.2 SSD.
HDMI Output	1 x HDMI v1.4a
Gigabit Ethernet Port	1 x Gigabit RJ45
USB Port	1 x USB 3.0 2 x USB 2.0
Audio	1 x Built-in speaker 1 x 3.5mm line out jack Note: You cannot use the speakers and the line-out jack simultaneously.
LED Indicators	Status/Power, LAN, USB, HDD 1-3, M.2 SSD 1-2
Buttons	Power, Reset, USB One-touch-copy
System Warning	Buzzer or Smart voice prompt
Form Factor	Tower
Dimensions (H x W x D)	142 x 150 x 260.1 mm 5.59 x 5.9 x 10.24 inch
Power Consumption (W)	HDD standby: 13.21 W In operation: 25.63 W (with 3 x HDDs and 2 x M.2 SSDs) HDD: WD10EFRX M.2 SSD: INTEL SSDPEKKW12 128G
Sound Level	Sound pressure (LpAm): 21.8 dB(A)

Weight	Net weight: 1.64 kg (3.62 lbs) Gross Weight: 2.69 kg (5.93 lbs)
Operating Temperature & Relative Humidity	0 ~ 40°C (32°F ~ 104°F), 5 ~ 95% RH non-condensing, wet bulb: 27°C (80.6°F)
Security Slot	Kensington security slot
Fan	1 x 9cm smart fan (12V DC)
Power Supply Unit	65W AC Adapter, 100-240V

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.