

Thunder



Thunder – let it crack!

For those who like design, the Thunder with its slightly tinted side panel made of Plexiglas and the switchable LED light on the front is the ideal candidate for a PC system with trendy LED lighting and a 120mm fan with blue LED lighting at the back as standard. Two additional installation options for 120mm fans in the front also improve the airflow in the case.

On the top of the case are USB 2.0 and 3.0 ports, the HD audio jacks and the LED button, with which the LED lighting in the front panel can be manually switched on and off. A removable dust filter under the power supply and a variety of ways to lay the cables, complete the offer.

- √ trendy LED lighting in the front panel
- √ modern design
- ✓ blue illuminated 120mm LED fan as standard
- √ Side panel made of Plexiglas



Thunder

Specifications

| <u>Specifications</u> | |
|-------------------------------|---|
| Motherboard | ATX, μATX, ITX |
| Max. drive bays | 5.25" external: 0 |
| | 3.5" external: 0 |
| | 3.5" internal: 2 |
| Fuert servestore | 2.5" internal: 2 USB 3.0: 1 |
| Front connectors | USB 3.0: 1 USB 2.0: 2 |
| | Microphone: 1 |
| | Speaker: 1 |
| Cooling system | Front: 2x 120mm |
| - , | (optional) |
| | Rear: 1x 120mm (serial, blue LEDs, 3pin and Molex connector) |
| Max CPU-Cooler height | (Serial, blue LEDS, Spill and Molex Conflector) |
| Max Graphic card length | 330mm |
| Packing units | Shipping unit: 1 pcs |
| | Packing unit: 28 pcs |
| Warranty | 24 Months |
| Article number | 88881309 |
| EAN-Code Scope of Delivery | 4260455643634 Screw set |
| Scope of Belivery | Speaker |
| Features | Front panel with blue LED strip |
| | Tinted window side panel |
| | 1x 120mm fan with blue LEDs on the back as standard |
| | LED button to switch the LED strip in the front panel on and off |
| | Two 3.5" bays below the motherboard carrier with separate airflow Place for water cooling in sizes of 120mm and 240mm |
| | Power supply mounting in a separate cage in the bottom part |
| | Openings for easy laying of cables |
| | Easy-to-remove dust filter below the power supply |
| | Stands |
| | |

Dimensions and Weight

| | Cage | Case | Package | |
|--|-------|-------|---------|--|
| Height | 410mm | 425mm | 460mm | |
| Width | 180mm | 195mm | 220mm | |
| Depth | 370mm | 410mm | 465mm | |
| Weight (net): 3.06 Kg Weight (gross): 3.82 Kg | | | | |

| ower Supply | L | |
|------------------------|----------|-------------|
| Connector | Quantity | Max. Length |
| Mainboard 20+4Pin | - | - |
| P4 12V 4Pin | - | - |
| P4/EPS 4+4Pin | - | 4 |
| P8 12V 8Pin | _ · _ | 417 |
| PCI-Express 6+2Pin | | |
| PCI-Express n IDE 4Pin | tho | - |
| S-ATA | - | - |
| Floppy | - | - |
| RPM sensor cable | - | - |
| Fan Control | - | - |
| Fan: 120mm | - | - |
| | | |

Certification:

