



## Equip 128352 USB 3.2 Gen 2 C naar C-kabel, 2,0 m, PD 60W, 4K/60Hz, 5Gbps, Wit

**Merk :** Equip

**Artikelcode:** 128352

**Productnaam :** 128352 USB 3.2 Gen 2 C naar C-kabel, 2,0 m, PD 60W, 4K/60Hz, 5Gbps, Wit

- "

- USB 3.2 Gen 2
  - Male naar Male
  - 5Gbps gegevensoverdrachtsnelheid
  - met E-mark chipset
  - Uitgangsstroom tot 3A, 20V/3A = 60W Max
  - Ondersteuning van USB Power Delivery (PD)
  - Resolutie: tot 4K@60 Hz
  - Verguld
  - Maatfel: PVC
  - Dubbele afscherming voor foutloze gegevensoverdracht"
- USB 3.2 Gen 2 C naar C-kabel, 2,0 m, PD 60W, 4K/60Hz, 5Gbps, Wit



**Equip 128352 USB 3.2 Gen 2 C naar C-kabel, 2,0 m, PD 60W, 4K/60Hz, 5Gbps, Wit:**

De equip® Platinum USB-C kabel met maximaal 3A (60W) vermogen, kunt u deze USB-C naar C kabel gebruiken om een USB-C laptop, zoals uw Apple MacBook Pro, MacBook of Chromebook Pixel™, van stroom te voorzien en op te laden met behulp van een USB-C muurlader, autolader of powerbank. Of je kunt je laptop van stroom voorzien via een USB-C dockingstation.

Equip 128352 USB 3.2 Gen 2 C naar C-kabel, 2,0 m, PD 60W, 4K/60Hz, 5Gbps, Wit. Snoerlengte: 2 m.

Aansluiting 1: USB C, Aansluiting 2: USB C, USB-versie: USB 3.2 Gen 2 (3.1 Gen 2), Max.

overdrachtssnelheid: 10 Gbit/s, Contact geleider materiaal: Nikkel, Kleur van het product: Wit

Features		Weight & dimensions	
USB version *	USB 3.2 Gen 2 (3.1 Gen 2)	Cable length *	2 m
Connector 1 *	USB C	Width	12.2 mm
Connector 2 *	USB C	Depth	33 mm
Connector 1 gender *	Male	Height	2000 mm
Connector 2 gender *	Male	Weight	6.4 kg
Connector 1 form factor	Straight	<b>Packaging data</b>	
Connector 2 form factor	Straight	Package width	180 mm
Connector contacts plating	Nickel	Package depth	220 mm
Reversible connectors	✓	Package height	13 mm
Cable jacket material	Thermoplastic elastomer (TPE)	Package weight	7.4 kg
Maximum data transfer rate	10000 Mbit/s	<b>Certificates</b>	
Maximum data transfer rate	10 Gbit/s	Compliance certificates	RoHS
Product colour *	White	Certification	CE
Plug and Play	✓	<b>Logistics data</b>	
<b>Power</b>		Harmonized System (HS) code	84733080
Output current (max)	3 A		



4015867205136

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-FEB-2025. Prints or copies of Information are only valid on the printed Publication date