TP-Link Deco M9 Plus Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 5 (802.11ac) Wit 2 Intern

Merk : TP-Link

Artikelcode: DECO M9 PLUS(2-PACK)

Productnaam : Deco M9 Plus

TP-Link Deco M9 Plus. Kleur van het product: Wit, Soort antenne: Intern, Type product: Mesh-systeem. Wifi-band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Wifi-standaard: Wi-Fi 5 (802.11ac), WLAN gegevensoverdrachtsnelheid (max): 2200 Mbit/s. Firewall: SPI, Ondersteunde mobiele besturingssystemen: Android 4.4, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2,..., Firmware kan geüpgraded worden via: Netwerk, USB. AC-ingangsspanning: 100 - 240 V, Ingangsstroom AC-adapter: 0,8 A, AC-ingangsfrequentie: 50 - 60 Hz. Certificering: FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC

Design

Product type	Mesh system
Product colour *	White
LED indicators	Power
Antenna type *	Internal
Antennas quantity	8
Reset button	✔

Wireless LAN features

Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)
WLAN data transfer rate (max) *	2200 Mbit/s
WLAN data transfer rate (first band)	400 Mbit/s
WLAN data transfer rate (second band)	867 Mbit/s
WLAN data transfer rate (third band)	867 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u
Security algorithms	WPA-PSK, WPA2-PSK
Number of guest networks (5 GHz)	1
Number of guest networks (2.4 GHz)	1
Dynamic IP	✔
Static IP	✔
Dynamic DNS (DDNS)	✔
Guest access	✔

Features

Mobile operating systems supported	Android 4.4, Android 5.0, Android 5.1, Android 6.0, Android 7.0, Android 7.1, Android 7.1.2, Android 8.0, Android 9.0, iOS 10.0, iOS 11.0, iOS 11.4, iOS 12, iOS 13, iOS 9.0, iOS 9.1, iOS 9.2, iOS 9.3
Parental control	✔
Firmware upgradeable via	Network, USB

Ports & interfaces

Ethernet LAN (RJ-45) ports *	2
Ethernet WAN	✔
DC-in jack	✔

Power

AC input voltage	100 - 240 V
AC adapter input current	0.8 A
AC input frequency	50 - 60 Hz
AC adapter output voltage	12 V
AC adapter output current	2 A

Certificates

Certification	FCC, IC, NCC, BSMI, IDA, RCM, JPA, JRF, VCCI, KC

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	144 mm

Features

Processor cores	4
Bluetooth	✔
Bluetooth version	4.2
Quality of Service (QoS) support	✔
Port forwarding	✔
Firewall security	SPI
BeamForming	✔
DHCP client	✔
DHCP server	✔

Weight & dimensions

Depth	144 mm
Height	64 mm

Packaging content

Number of products included	2 pc(s)
AC adapter included	✔
Number of units included	2 pc(s)
Ethernet cable	✔

Packaging data

Package width	319 mm
Package depth	238 mm
Package height	110 mm
Package weight	1.4 kg

Logistics data

Harmonized System (HS) code	85176990

6935364083175