

ASUS ZenWiFi Pro ET12 Tri-band (2,4 GHz / 5 GHz / 6 GHz) Wi-Fi 6E (802.11ax) Zwart 3 Intern

Merk : ASUS

Artikelcode: 90IG05Z0-MO3A20

Productnaam : ZenWiFi Pro ET12

ASUS ZenWiFi Pro ET12. Kleur van het product: Zwart, Soort antenne: Intern, LED-indicatoren: Stroom, Status. Wifi-band: Tri-band (2,4 GHz / 5 GHz / 6 GHz), Wifi-standaard: Wi-Fi 6E (802.11ax), Wi-Fi-standaarden: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E.... Frequentie van processor: 2 GHz, Flash memory: 256 MB, Firewall: Keyword filter, Network service filter, URL filter. AC-ingangsspanning: 110 - 240 V, AC-ingangsfrequentie: 50 - 60 Hz, AC-adapter, uitgangsspanning: 19 V. Breedte: 115 mm, Diepte: 115 mm, Hoogte: 241 mm



Design		Kenmerken	
Kleur van het product *	Zwart	Firewall	Keyword filter, Network service filter, URL filter
LED-indicatoren	Stroom, Status	BeamForming	✓
Soort antenne *	Intern	Ouderlijk toezicht	✓
Antennas quantity	10	SSID Broadcast	✓
Reset button	✓	MU-MIMO-technologie	✓
Draadloos LAN		Poorten & interfaces	
Wifi-band *	Tri-band (2,4 GHz / 5 GHz / 6 GHz)	Aantal Ethernet LAN (RJ-45)-poorten *	3
Wifi-standaard *	Wi-Fi 6E (802.11ax)	Ethernet WAN	✓
Wi-Fi-standaarden	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)	Aansluiting voor netstroomadapter	✓
WLAN gegevensoverdrachtsnelheid (eerste band)	1148 Mbit/s	Energie	
WLAN gegevensoverdrachtsnelheid (tweede band)	4804 Mbit/s	AC-ingangsspanning	110 - 240 V
WLAN-gegevensoverdrachtsnelheid (derde band)	4804 Mbit/s	AC-ingangsfrequentie	50 - 60 Hz
Netwerkstandaard	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g	AC-adapter, uitgangsspanning	19 V
Ondersteunde beveiligingsalgoritmen	WPA3-PSK, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK	AC-adapter, uitgangsstroom	2,37 A
IGMP snooping	✓	Gewicht en omvang	
Dynamic DNS (DDNS)	✓	Breedte	115 mm
Toegang voor gasten	✓	Diepte	115 mm
VPN eigenschappen	VPN Client L2PT VPN Client OVPN VPN Client PPTP VPN Server IPsec VPN Server OVPN VPN Server PPTP	Hoogte	241 mm
Kenmerken		Gewicht	1,5 kg
Type processor	✓	Verpakking	
Frequentie van processor	2 GHz	Breedte verpakking	434 mm
Flash memory	256 MB	Diepte verpakking	280 mm
Quality of Service (QoS)	✓	Hoogte verpakking	165 mm
		Gewicht verpakking	4,5 kg
		Logistieke gegevens	
		Code geharmoniseerd systeem (HS) 85171800	



4711081440178

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-NOV-2024. Prints or copies of Information are only valid on the printed Publication date