



## PDU SW-0816

The **PDU** (**P**ower **D**istribution **U**nit) **SW-0861** is a switchable power board, intended for installation in 19" server cabinets, which can be operated over web interface.

Thus, all 8 outputs can be switched individually by remote access, as well as the total current consumption, total voltage, temperature and humidity can be queried via the web interface.

The built-in display and the function key displays the temperature, humidity, total power consumption and input voltage.

## **Specifications**

Connectors	Power In (C20): 1 Power Out (C13): 8 RJ45 (LAN): 1
Controls	Automatic Cutout
LED / LED Display	Power Link Range
Materials	1.2mm Steel
Dimensions <small>(H/W/D)</small>	44.5/442/135mm
Package Dimension <small>(H/W/D)</small>	87/497/207mm
Weight <small>(net)</small>	2.02kg
Weight <small>(gross)</small>	2.43kg
Packing Unit	Shipping Unit: 1 piece
Guarantee and Warranty	24 Months Warranty
Artikel Number	88887284
EAN-Code	4260455644532
Scope of Delivery	Mounting Kit Connection Cable C20/C19 (2m) "PDU Utility", German manual on CD
Features	Measurement of current, voltage and output Temperature and humidity sensor installed E-mail notification over the Windows control software Webinterface HTTP, DHCP Adjustable Alarm function Maximum input current 16A Maximum output current 16A (total) Switching current per socket max. 10A

**Certification:**

