## Philips 242B9T/00 computer monitor 60,5 cm (23.8") 1920 x 1080 Pixels Full HD LCD Tafelblad Zwart

Merk : Philips

Artikelcode: 242B9T/00

Productnaam : 242B9T/00

Monitor 242B9T LCD-monitor met SmoothTouch

## Philips 242B9T/00 computer monitor 60,5 cm (23.8") 1920 x 1080 Pixels Full HD LCD Tafelblad Zwart:

Een stevig touchscreen dat water- en stofbestendig is en overal kan worden gebruikt, met een standaard die u naar wens kunt aanpassen. Dankzij de apps is de bediening van het scherm eenvoudig en intuïtief, zodat u zeer productief kunt zijn.

Philips 242B9T/00. Beeldschermdiagonaal: 60,5 cm (23.8"), Resolutie: 1920 x 1080 Pixels, HD type: Full HD, Display technologie: LCD, Beeldoppervlakte: Glans, Responstijd: 5 ms, Oorspronkelijke beeldverhouding: 16:9, Kijkhoek, horizontaal: 178°, Kijkhoek, verticaal: 178°. Ingebouwde luidsprekers. Ingebouwde USB-hub, Versie USB-hub: 3.2 Gen 1 (3.1 Gen 1). VESA-montage, In hoogte verstelbaar. Kleur van het product: Zwart






## Display

Display diagonal *	60.5 cm
Display resolution *	1920 x 1
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Backlight type	W-LED
Touchscreen *	×
Touchscreen type	Tabletop
Touchscreen technology	Capacitiv
Touch technology	Multi-tou
Number of simultaneous touchpoints	10
Display brightness (typical)	250 cd/m
Display brightness	250 cd/m
Response time *	5 ms
Display surface	Gloss
Screen shape *	Flat
Aspect ratio	16:9
Contrast ratio (typical) *	1000:1
Contrast ratio (dynamic)	5000000
Dynamic contrast ratio marketing name	SmartCo
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.78 mi
Pixel pitch	0.275 x (
Pixel density	93 ppi
Horizontal scan range	30 - 85 k
Vertical scan range	48 - 75 H
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm

60.5 cm (23.8")	Wal
1920 x 1080 pixels	Cab
Full HD	Cab
16:9	Hei
LCD	Adj
IPS	Pivo
W-LED	Swi
×	
Tabletop	Tilt
Capacitive	Tilt
Multi-touch	
10	On
250 cd/m²	
250 cd/m <sup>2</sup>	
5 ms	Nur
Gloss	Plug
Flat	LED
16:9	Pov
1000:1	Ene
5000000:1	Ene
SmartContrast	hou
60 Hz	Pov
178°	Pov
178°	Pov
16.78 million colours	Pov
0.275 x 0.275 mm	AC
93 ppi	AC
30 - 85 kHz	Pov
48 - 75 Hz	Ene
52.7 cm	Eur Ene

Ergonomics	
Wall mountable	<ul> <li>Image: A set of the set of the</li></ul>
Cable lock slot *	<i>✓</i>
Cable lock slot type	Kensington
Height adjustment *	✓
Adjustable height (max)	18.4 cm
Pivot	×
Swivelling	×
Tilt adjustment	✓
Tilt angle range	-5 - 90°
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Number of OSD languages	20
Plug and Play	✓
LED indicators	Power, Stand-by
Power	
Energy efficiency class (SDR) *	E
Energy consumption (SDR) per 1000 hours *	18 kWh
Power consumption (typical) *	16 W
Power consumption (standby) $^{st}$	0.5 W
Power consumption (off)	0.3 W
Power consumption (PowerSave)	11.5 W
AC input voltage	100-240
AC input frequency	50-60 Hz
Power supply type	AC A to G
Power supply type Energy efficiency scale European Product Registry for	AC A to G

P1 - 1			
Display		Operational conditions	
Digital horizontal frequency	30 - 85 kHz	Operating temperature (T-T)	0 - 40 °C
Digital vertical frequency	48 - 75 Hz	Storage temperature (T-T)	-20 - 60 °C
Sync-on-green (SOG)	1	Operating relative humidity (H-H)	20 - 80%
Display diagonal (metric)	60.5 cm	Operating altitude	0 - 3658 m
DDC/CI	4	Non-operating altitude	0 - 12192 m
Surface hardness	7H	Weight & dimensions	
Colour gamut standard	sRGB	Width (with stand)	554 mm
Colour gamut	72%	Depth (with stand)	227 mm
NTSC coverage (typical)	72%	Height (with stand)	413 mm
3D	×	Weight (with stand)	8.15 kg
Separate H/V sync	1	Width (without stand)	554 mm
Display sRGB	1	Depth (without stand)	50 mm
Performance		Height (without stand)	338 mm
NVIDIA G-SYNC *	×	Weight (without stand)	4.86 kg
AMD FreeSync *	×	Packaging data	
AND TRESSIC	Separate sync, Sync-on-green	Package width	620 mm
Component video sync	(SOG)	Package depth	168 mm
Flicker-free technology	1	Package height	433 mm
Low Blue Light technology	1	Package weight	11.1 kg
Windows operating systems	Windows 10, Windows 7, Windows	Package type	Box
supported	8, Windows 8.1	Packaging content	
OmniTapps Multitouch compatibility	×	Stand included	1
Multimedia			VGA, HDMI, DisplayPort, USB Type-A
	2	Cables included	to USB Type-B, Audio (3.5mm), AC
Number of speakers	2	Manual	1
RMS rated power	4 W	Bundled software	SmartControl
Built-in speaker(s) *		Sustainability	
Built-in microphone	×	Sustainability certificates	ENERGY STAR
Built-in camera *	×	Doesn't contain	PVC/BFR, Mercury
Design			
Market positioning *	Home	Other features	
Product colour *	Black	International Protection (IP) code	IP54
Front bezel colour	Black	Rotating	×
Feet colour	Black	TV tuner integrated	×
Ports & interfaces		Exterior finish type	Textured
Built-in USB hub *	1	Package dimensions (WxDxH)	620 x 433 x 168 mm
USB hub version	• 3.2 Gen 1 (3.1 Gen 1)	Display viewable area (HxV)	527 x 296.5 mm
USB Type-A downstream ports		Recyclable packaging material	100%
quantity	2	Mobile operating systems supported	Android 7.1, Android 7.0, Android 6.0, Android 5.0, Android 4.4
VGA (D-Sub) ports quantity	1	Heavy metals free	Hg (mercury)
DVI port	1	Folding angle	70°
DVI-D ports quantity	1	EasyRead mode	1
HDMI *	1	Recommended resolution	1920 x 1080 @ 60 Hz
HDMI ports quantity	1.4	Picture enhancement	SmartImage
HDMI version	1.4		CB; CE Mark; FCC Class B; SEMKO;
DisplayPorts quantity	1.2	Regulatory Approvals	UKRAINIAN; ICES-003; TUV/GS; TUV
DisplayPort version	1.2	Touch moths -	Ergo; CU-EAC; EAEU RoHS; cETLus
Audio input	1	Touch method	Stylus, Finger, Glove
Headphone out *	1	LowBlue mode	
Headphone outputs	1	Energy efficiency class (old)	A
PC Audio in	1	Compliance certificates	RoHS
HDCP	1	Mean time between failures (MTBF)	70000 h
HDCP version	1.4	Certification	CE Mark, FCC Class B, SEMKO, EPA, UKRAINIAN, ICES-003, TUV/GS, TUV
			Ergo, CU-EAC
Ergonomics		Logistics data	
VESA mounting *	1	Harmonized System (HS) code	85285210
Panel mounting interface	100 x 100 mm		





8712581756802

0609585252875



609585252875

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.