

ASUS ZenWiFi AX (XT9) AX7800 1er Pack Weiß Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Wit 4 Intern

Merk : ASUS

Artikelcode: 90IG0740-MO3B60

Productnaam : ZenWiFi AX (XT9) AX7800 1er Pack
Weiß

ASUS ZenWiFi AX (XT9) AX7800 1er Pack Weiß. Kleur van het product: Wit, Soort antenne: Intern, Type product: Mesh-systeem. Wifi-band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Wifi-standaard: Wi-Fi 6 (802.11ax), Wi-Fi-standaarden: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Frequentie van processor: 1,7 GHz, Intern geheugen: 512 MB, Flash memory: 256 MB. AC-ingangsspanning: 110 - 240 V, AC-ingangsfrequentie: 50 - 60 Hz, AC-adaptor, uitgangsspanning: 12 V. Gewicht: 740 g



Design		Kenmerken	
Type product	Mesh-systeem	Type processor	✓
Kleur van het product *	Wit	Aantal processorkernen	2
LED-indicatoren	Stroom	Frequentie van processor	1,7 GHz
Soort antenne *	Intern	Intern geheugen	512 MB
Antennas quantity	6	Flash memory	256 MB
Maximale dekking	264,77 m ²	Quality of Service (QoS)	✓
Reset button	✓	Ouderlijk toezicht	✓
Draadloos LAN		Functies voor ouderlijk toezicht	Aangepaste profielen
Wifi-band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)	Firmware kan geüpgraded worden via	Wizard voor automatische upgrade
Wifi-standaard *	Wi-Fi 6 (802.11ax)	Bedrijfsmodi	Wireless router mode, Access point mode
Wi-Fi-standaarden	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Poorten & interfaces	
WLAN gegevensoverdrachtsnelheid (eerste band)	574 Mbit/s	Aantal Ethernet LAN (RJ-45)-poorten *	4
WLAN gegevensoverdrachtsnelheid (tweede band)	2402 Mbit/s	Ethernet WAN	✓
WLAN-gegevensoverdrachtsnelheid (derde band)	4804 Mbit/s	Energie	
Netwerkstandaard	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11g, IEEE 802.11n	AC-ingangsspanning	110 - 240 V
Ondersteunde beveiligingsalgoritmen	WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3-PSK, WPS	AC-ingangsfrequentie	50 - 60 Hz
IGMP snooping	✓	AC-adaptor, uitgangsspanning	12 V
Dynamic DNS (DDNS)	✓	AC-adaptor, uitgangsstroom	3 A
Toegang voor gasten	✓	Gewicht en omvang	
VPN eigenschappen	Instant Guard VPN Client L2TP VPN Client OVPN VPN Client PPTP VPN Client WireGuard VPN Server IPSec VPN Server OVPN VPN Server PPTP VPN Fusion VPN Server WireGuard	Gewicht	740 g
		Inhoud van de verpakking	
		Inclusief AC-adaptor	✓
		Ethernetkabel	✓



4711081471479

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-NOV-2024. Prints or copies of Information are only valid on the printed Publication date