



Kingston Technology FURY Beast 16GB 5200MT/s DDR5 CL40 DIMM RGB

Merk : Kingston Technology

Productfamilie: FURY

Artikelcode:
KF552C36BBEA-16



Productnaam : 16GB 5200MT/s
DDR5 CL40 DIMM FURY Beast
RGB



- Verbeterde RGB-verlichting met nieuw ontwerp voor warmteverspreiding*
- Gepatenteerde Kingston FURY Infrared Sync Technology™
- Gecertificeerd voor Intel® XMP 3,0
- Gecertificeerd voor AMD EXPO™
- Gekwalificeerd door 's werelds toonaangevende fabrikanten van moederborden**
- Verbeterde stabiliteit voor overklokken

16GB 5200MT/s DDR5 CL40 DIMM FURY Beast RGB

Kingston Technology FURY Beast 16GB 5200MT/s DDR5 CL40 DIMM RGB. Component voor: PC, Intern geheugen: 16 GB, Geheugenlayout (modules x formaat): 1 x 16 GB, Intern geheugentype: DDR5, Kloksnelheid geheugen: 2600 MHz, Geheugen form factor: 288-pin DIMM, CAS-latentie: 36

| Features | | Features | |
|---|---------------------------|----------------------------------|----------------|
| Buffered memory type | Unregistered (unbuffered) | Cooling type | Heatsink |
| On-Die ECC | ✓ | Lead plating | Gold |
| CAS latency | 36 | Backlight | ✓ |
| Internal memory * | 16 GB | Backlight colour | Red/Green/Blue |
| Memory layout (modules x size) * | 1 x 16 GB | JEDEC standard | ✓ |
| Internal memory type * | DDR5 | Operational conditions | |
| Memory clock speed * | 2600 MHz | Operating temperature (T-T) | 0 - 85 °C |
| Memory data transfer rate | 5200 MT/s | Storage temperature (T-T) | -55 - 100 °C |
| Component for * | PC | Weight & dimensions | |
| Memory form factor * | 288-pin DIMM | Width | 7.11 mm |
| ECC * | ✗ | Depth | 133.3 mm |
| Memory ranking | 1 | Height | 42.2 mm |
| Memory voltage | 1.25 V | Weight | 42.38 g |
| Module configuration | 2048M x 64 | Packaging data | |
| Row cycle time | 48 ns | Package width | 57.1 mm |
| Refresh row cycle time | 295 ns | Package depth | 14 mm |
| Row active time | 32 ns | Package height | 171.4 mm |
| AMD Extended Profiles for Overclocking (EXPO) | ✓ | Package weight | 63.55 g |
| AMD Extended Profiles for Overclocking (EXPO) version | 1.0 | Logistics data | |
| SPD profile | ✓ | Master (outer) case width | 193 mm |
| Programming power voltage (VPP) | 1.8 V | Master (outer) case length | 325.1 mm |
| Country of origin | China, Taiwan | Master (outer) case height | 88.9 mm |
| | | Master (outer) case gross weight | 1.82 kg |
| | | Products per master (outer) case | 25 pc(s) |



0740617330908



740617330908

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.