TP-Link Deco XE75 Pro Tri-band (2,4 GHz / 5 GHz / 6 GHz) Wi-Fi 6E (802.11ax) Wit 3 Intern

Merk : TP-Link

Productnaam : Deco XE75 Pro

**Artikelcode:** DECO XE75 PRO(1-PACK)

TP-Link Deco XE75 Pro. Kleur van het product: Wit, Soort antenne: Intern, Type product: Netwerkrouter. Wifi-band: Tri-band (2,4 GHz / 5 GHz / 6 GHz), Wifi-standaard: Wi-Fi 6E (802.11ax), Wi-Fi-standaarden: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E.... Frequentie van processor: 1,7 GHz, Firewall: SPI Firewall, Functies voor ouderlijk toezicht: Bedtijd, Inhoudsfilter, Aangepaste profielen, Tijd met familie, Pause the Internet, Tijdcontroles,.... AC-ingangsspanning: 100 - 240 V, AC-ingangsfrequentie: 50 - 60 Hz, AC-adapter, uitgangsspanning: 12 V. Certificering: CE, FCC, RoHS

Design

Product type	Mesh router
Product colour *	White
LED indicators	Yes
Antenna type *	Internal
Antennas quantity	4
Maximum coverage	270 m²
Transmit power	FCC: <30 dBm (2.4 GHz), <30 dBm (5 GHz), <30 dBm (6 GHz), CE: <20 dBm (2.4 GHz), <23 dBm (5 GHz), <23 dBm (6 GHz)
Reset button	✔

Wireless LAN features

Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 6 GHz)
Top Wi-Fi standard *	Wi-Fi 6E (802.11ax)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)
WLAN data transfer rate (first band)	574 Mbit/s
WLAN data transfer rate (second band)	2402 Mbit/s
WLAN data transfer rate (third band)	2402 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Security algorithms	WPA, WPA2-PSK, WPA3
Number of guest networks (5 GHz)	1
Number of guest networks (2.4 GHz)	1
Point-to-point protocol over Ethernet (PPPoE)	✔

Features

Quality of Service (QoS) support	✔
Port forwarding	✔
Firewall security	SPI Firewall
BeamForming	✔
DHCP client	✔
DHCP server	✔
Universal Plug and Play (UPnP)	✔
Parental control	✔
Parental control features	Bedtime, Content filter, Custom profiles, Family time, Pause the Internet, Time controls, Time rewards, Weekly/monthly reports
MU-MIMO technology	✔
MIMO	✔

Protocols

Supported network protocols (IPv6)	✔

Ports & interfaces

Ethernet LAN (RJ-45) ports *	3
Ethernet WAN	✔
DC-in jack	✔

Power

AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
AC adapter output voltage	12 V

Certificates

Certification	CE, FCC, RoHS

Wireless LAN features

Dynamic IP	✔
Static IP	✔
Wireless Distribution System (WDS) bridge	✔
IGMP proxy	✔
IGMP snooping	✔
Tagged VLAN	✔
Dynamic DNS (DDNS)	✔
Guest access	✔
Apps supported	TP-Link Deco

Features

Built-in processor	✔
Processor cores	4
Processor frequency	1.7 GHz

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	105 mm
Depth	105 mm
Height	169 mm

Packaging content

Number of products included	1 pc(s)
AC adapter included	✔
Number of units included	1 pc(s)
Ethernet cable	✔

4897098685006

4897098684979