

ASUS ROG Rapture GT6 (W-2-PK) Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Wit 4 Intern

Merk : ASUS

Artikelcode: 90IG07F0-MU9A40

Productnaam : ROG Rapture GT6 (W-2-PK)

ASUS ROG Rapture GT6 (W-2-PK). Kleur van het product: Wit, Soort antenne: Intern, Type product: Netwerkrouter. Wifi-band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Wifi-standaard: Wi-Fi 6 (802.11ax), Wi-Fi-standaarden: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Frequentie van processor: 1,7 GHz, Intern geheugen: 512 MB, Flash memory: 256 MB. AC-ingangsspanning: 110 - 240 V, AC-ingangsfrequentie: 50 - 60 Hz, AC-adapter, uitgangsspanning: 19 V. Breedte: 172,3 mm, Diepte: 78,1 mm, Hoogte: 176,8 mm



Design		Features	
Product type	Mesh router	Internal memory	512 MB
Product colour *	White	Flash memory	256 MB
LED indicators	Power	Quality of Service (QoS) support	✓
Antenna type *	Internal	BeamForming	✓
Antennas quantity	9	DHCP server	✓
Maximum coverage	538.8 m²	Parental control	✓
Reset button	✓	SSID Broadcast	✓
Wireless LAN features		MU-MIMO technology	✓
Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)	Ports & interfaces	
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Ethernet LAN (RJ-45) ports *	4
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Ethernet WAN	✓
WLAN data transfer rate (first band)	574 Mbit/s	DC-in jack	✓
WLAN data transfer rate (second band)	4804 Mbit/s	Power	
WLAN data transfer rate (third band)	4804 Mbit/s	AC input voltage	110 - 240 V
Networking standards	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	AC input frequency	50 - 60 Hz
Security algorithms	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3	AC adapter output voltage	19 V
Point-to-point protocol over Ethernet (PPPoE)	✓	AC adapter output current	2.37 A
IGMP snooping	✓	Weight & dimensions	
Dynamic DNS (DDNS)	✓	Width	172.3 mm
VPN support	VPN Client L2TP VPN Client OVPN	Depth	78.1 mm
	VPN Client PPTP VPN Client	Height	176.8 mm
	WireGuard VPN Server IPSec VPN	Weight	880 g
	Server OVPN VPN Server PPTP VPN Server WireGuard VPN Fusion	Packaging content	
		Number of products included	2 pc(s)
		Ethernet cable	✓

Features		Packaging data	
Built-in processor	✓	Package width	425 mm
Processor cores	3	Package depth	280 mm
Processor frequency	1.7 GHz	Package height	140 mm
		Package weight	3.72 kg



4711081798583

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-FEB-2025. Prints or copies of Information are only valid on the printed Publication date