

ASUS ROG Rapture GT6 AX10000 AiMesh 1 Pack Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Zwart 4 Intern

Merk : ASUS

Artikelcode: 90IG07F0-MU9A10

Productnaam : ROG Rapture GT6 AX10000 AiMesh 1 Pack

ASUS ROG Rapture GT6 AX10000 AiMesh 1 Pack. Kleur van het product: Zwart, Soort antenne: Intern, Type product: Netwerkrouter. Wifi-band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Wifi-standaard: Wi-Fi 6 (802.11ax), Wi-Fi-standaarden: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Frequentie van processor: 1,7 GHz, Intern geheugen: 512 MB, Flash memory: 256 MB. AC-ingangsspanning: 110 - 240 V, AC-ingangsfrequentie: 50 - 60 Hz, AC-adapter, uitgangsspanning: 19 V. Breedte: 172,3 mm, Diepte: 78,1 mm, Hoogte: 176,8 mm



Design		Features	
Product type	Mesh router	Processor frequency	1.7 GHz
Product colour *	Black	Internal memory	512 MB
LED indicators	Power	Flash memory	256 MB
Antenna type *	Internal	Quality of Service (QoS) support	✓
Antennas quantity	9	BeamForming	✓
Maximum coverage	538.8 m²	DHCP server	✓
Reset button	✓	Parental control	✓
Wireless LAN features		SSID Broadcast	✓
Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)	MU-MIMO technology	✓
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Ports & interfaces	
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Ethernet LAN (RJ-45) ports *	4
WLAN data transfer rate (first band)	574 Mbit/s	Ethernet WAN	✓
WLAN data transfer rate (second band)	4804 Mbit/s	DC-in jack	✓
WLAN data transfer rate (third band)	4804 Mbit/s	Power	
Networking standards	IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	AC input voltage	110 - 240 V
Security algorithms	WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3	AC input frequency	50 - 60 Hz
Point-to-point protocol over Ethernet (PPPoE)	✓	AC adapter output voltage	19 V
IGMP snooping	✓	AC adapter output current	2.37 A
Dynamic DNS (DDNS)	✓	Weight & dimensions	
VPN support	VPN Client L2TP VPN Client OVPN VPN Client PPTP VPN Client WireGuard VPN Server IPSec VPN Server OVPN VPN Server PPTP VPN Server WireGuard VPN Fusion	Width	172.3 mm
Features		Depth	78.1 mm
Built-in processor	✓	Height	176.8 mm
Processor cores	3	Weight	880 g
		Packaging content	
		Number of products included	1 pc(s)
		Ethernet cable	✓
		Packaging data	
		Package width	425 mm
		Package depth	280 mm
		Package height	140 mm



4711081798552

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-FEB-2025. Prints or copies of Information are only valid on the printed Publication date