


ASUS P12R-I/ASMB10 Intel C252 LGA 1200 (Socket H5) ATX

Merk : ASUS

Artikelcode: 90SB0A70-M0UAY0

Productnaam : P12R-I/ASMB10

ASUS P12R-I/ASMB10. Processorfabrikant: Intel, Processor socket: LGA 1200 (Socket H5), Compatibele processors: Intel® Pentium®, Intel Xeon E. Ondersteunde geheugen types: DDR4-SDRAM, Maximum intern geheugen: 64 GB, Geheugen slots type: DIMM. Ondersteunde opslagstationinterfaces: M.2, SATA III. Grafische adapter-familie: ASPEED, Grafische adapter: AST2600, On-board graphics adapter geheugen: 64 MB. LAN controller: Intel® I210-AT



Processor		Aansluitingen achterzijde	
Processorfabrikant *	Intel	Aantal poorten USB 3.2 Gen 1 (3.1 Gen 1) Type A *	4
Processor socket *	LGA 1200 (Socket H5)	Aantal Ethernet LAN (RJ-45)-poorten *	3
Compatibele processors *	Intel® Pentium®, Intel Xeon E	VGA (D-Sub)poort(en) *	1
Geheugen		Aantal SAS-poorten	2
Ondersteunde geheugen types *	DDR4-SDRAM	Netwerk	
Aantal geheugenslots *	2	Ethernet LAN	✓
Geheugen slots type	DIMM	LAN controller	Intel® I210-AT
Geheugen kanaal	Dubbelkanaals	Wifi *	✗
Supported memory clock speeds	2666,2933,3200 MHz	Kenmerken	
Maximum intern geheugen *	64 GB	Chipset moederbord *	Intel C252
Ondersteunde geheugenmodule capaciteiten	4GB, 8GB, 16GB, 32GB	Component voor *	Server
Opslag-controllers		Moederbord form factor *	ATX
Ondersteunde opslagstationinterfaces *	M.2, SATA III	Moederbord chipset familie *	Intel
Grafisch		Uitbreidingsmodules	
Grafische adapter-familie	ASPEED	PCI Express x16 slots	1
Grafische adapter	AST2600	Aantal M.2 (M) slots	1
On-board graphics adapter geheugen	64 MB	Eisen aan de omgeving	
Interne aansluitingen		Temperatuur bij opslag	-40 - 70 °C
USB 3.2 Gen 1 (3.1 Gen 1)-aansluitingen *	1	Bedrijfstemperatuur (T-T)	10 - 50 °C
Aantal SATA III connectors *	6	Luchtvochtigheid bij opslag	20 - 90 procent
ATX Power connector (24-pin)	✓	Logistieke gegevens	
Aansluitingen voor behuizingsventilatoren	2	Code geharmoniseerd systeem (HS) 84733020	

Interne aansluitingen		Verpakking	
Chassis intrusion aansluiting	✓	Breedte verpakking	311 mm
EPS power connector (8-pin)	✓	Diepte verpakking	281 mm
TPM connector	✓	Hoogte verpakking	78 mm
Serial port headers	1	Gewicht verpakking	1,2 kg
		Gewicht en omvang	
		Breedte	170 mm
		Diepte	170 mm
		Overige specificaties	
		Gewicht	500 g



4711081507604

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.