

be quiet! Pure Power 12 M power supply unit 1000 W 20+4 pin ATX ATX Zwart

Merk : be quiet!

Artikelcode: BN345

Productnaam : Pure Power 12 M

be quiet! Pure Power 12 M. Totaal vermogen: 1000 W, AC-ingangsspanning: 100 - 240 V, Piekvermogen: 1050 W. Motherboard power connector: 20+4 pin ATX, Lengte stroomkabel moederbord: 55 cm, Lengte SATA-stroomkabel: 500,600,650,800,950 mm. Bedoeld voor: PC, Vormfactor van de voeding (PSU): ATX, 80 PLUS certificatie: 80 PLUS Gold. Kleur van het product: Zwart, Type koeling: Actief, Ventilator diameter: 12 cm. Meegeleverde kabels: PATA, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	1000 W	PCI Express connector	✓
Peak power	1050 W	Cabling type	Fully-Modular
AC input voltage *	100 - 240 V	Performance	
AC input frequency	50 - 60 Hz	80 PLUS certification *	80 PLUS Gold
Input current	12 / 6 A	Purpose *	PC
Power factor	0.98	Power supply unit (PSU) form factor *	ATX
Power Factor Correction (PFC) type	Active	ATX version	3.1
Combined power (+3.3V)	120 W	EPS version	2.92
Combined power (+12V)	1000 W	Noise level	31.7 dB
Combined power (+5V)	120 W	Mean time between failures (MTBF)	100000 h
Combined power (-12V)	3.6 W	Design	
Combined power (+5Vsb)	15 W	Product colour	Black
Max output current (+3.3V)	22 A	Cooling type	Active
Max output current (+12V)	83.4 A	Fan diameter	12 cm
Max output current (+12V1)	46 A	Number of fans	1 fan(s)
Max output current (+12V2)	42 A	Fan speed	0 - 2000 RPM
Max output current (+5V)	22 A	Fan location	Top
Max output current (-12V)	0.3 A	On/off switch	✓
Max output current (+5Vsb)	3 A	Operational conditions	
Efficiency	93.2%	Operating temperature (T-T)	0 - 40 °C
Power Good signal delay range	100 - 150 ms	Packaging content	
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit	Cables included	PATA, PCIe, Peripheral (Molex), SATA
Ports & interfaces		Certificates	
Motherboard power connector *	20+4 pin ATX	Compliance certificates	RoHS
Motherboard power cable length	55 cm	Weight & dimensions	
Number of SATA power connectors	6	Width	160 mm
Number of PATA power connectors	2	Depth	150 mm
SATA power cable length	500,600,650,800,950 mm	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	1	Packaging data	
Peripheral (Molex) power cable length	550 mm	Package type	Box
EPS power connector (8-pin)	✓		
EPS power connector (4+4 pin)	✓		

Ports & interfaces		Technical details	
PCI Express power connectors (6+2 pin)	4	Sustainability compliance	✓
PCI Express power cable length	65 cm	Sustainability certificates	ENERGY STAR, ErP
ATX power connector (20+4 pin)	✓	Logistics data	
		Warranty period	10 year(s)
		Other features	
		Screws included	✓
		Number of screws	5
		Cable ties included	✓
		Noise level (silent mode, <30%)	9.3 dB
		Noise level (quiet mode, 50%)	9.6 dB
		Noise level (full-load mode, 100%)	31.7 dB



4260052189504

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-MAR-2025. Prints or copies of Information are only valid on the printed Publication date