be quiet! Pure Power 12 M power supply unit 650 W 20+4 pin ATX ATX Zwart

Merk: be quiet! Artikelcode: BN342

Productnaam: Pure Power 12 M







Power		Ports & interfaces	
Total power *	650 W	Cabling type	Fully-Modular
Peak power	720 W	Performance	
AC input voltage *	100 - 240 V	80 PLUS certification *	80 PLUS Gold
AC input frequency	50 - 60 Hz	Purpose *	PC
Input current	10/5 A	Power supply unit (PSU) form factor	
Power factor	0.98	*	ATX
Power Factor Correction (PFC) type	Active	ATX version	3.1
Combined power (+3.3V)	120 W	EPS version	2.92
Combined power (+12V)	650 W	Noise level	19.9 dB
Combined power (+5V)	120 W	Mean time between failures (MTBF)	100000 h
Combined power (-12V) Combined power (+5Vsb)	3.6 W 15 W	Design	
Max output current (+3.3V)	20 A	Product colour	Black
Max output current (+12V1)	32 A	Cooling type	Active
Max output current (+12V2)	28 A	Fan diameter	12 cm
Max output current (+5V)	20 A	Number of fans	1 fan(s)
Max output current (-12V)	0.3 A	Fan location	Тор
Max output current (+5Vsb)	3 A	On/off switch	✓
Efficiency	92.7%	Operational conditions	
Power Good signal delay range	100 - 150 ms	Operating temperature (T-T)	0 - 40 °C
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit	Packaging content	0 - 40 C
Ports & interfaces		Cables included	PATA, PCIe, Peripheral (Molex),
Motherboard power connector *	20+4 pin ATX		SATA
Motherboard power cable length	55 cm	Certificates	
Number of SATA power connectors	5	Compliance certificates	RoHS
Number of PATA power connectors	2	Weight & dimensions	
SATA power cable length	500,650,800,950 mm	Width	160 mm
Peripheral (Molex) power connectors (4-pin) *	1	Depth	150 mm
Peripheral (Molex) power cable		Height	86 mm
length	550 mm	Packaging data	
EPS power connector (4+4 pin)	✓	Package type	Box
PCI Express power connectors (6+2 pin)	2	Technical details	
CPU P4 connector (4-pin)	1	Sustainability compliance	✓

Ports & interfaces		Technical details	
ATX power connector (20+4 pin)	✓	Sustainability certificates	ENERGY STAR, ErP
PCI Express connector		Logistics data	
		Warranty period	10 year(s)
		Other features	
		Screws included	✓
		Number of screws	5
		Cable ties included	✓
		Noise level (silent mode, <30%)	8.1 dB
		Noise level (quiet mode, 50%)	9.1 dB
		Noise level (full-load mode, 100%)	19.9 dB





4260052189474

4260052189771

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.