

StarTech.com CDP2DP141MB video kabel adapter 1 m DisplayPort USB Type-C Zwart

Merk : StarTech.com

Artikelcode: CDP2DP141MB

Productnaam : CDP2DP141MB

StarTech.com 1m - USB-C naar DisplayPort adapter kabel - 8K 30Hz - HBR3 - USB-C video adapter kabel - Thunderbolt™ 3 compatibel

[StarTech.com CDP2DP141MB video kabel adapter 1 m DisplayPort USB Type-C Zwart:](#)

USB-C video adapter kabel | Thunderbolt 3 compatibel | HBR3

The StarTech.com Advantage

StarTech.com CDP2DP141MB. Snoerlengte: 1 m, Aansluiting 1: DisplayPort, Aansluiting 2: USB Type-C. Gewicht: 38 g, Breedte: 200 mm, Diepte: 1000 mm. Aantal per verpakking: 1 stuk(s), Breedte verpakking: 200 mm, Diepte verpakking: 220 mm. (Buitenste) hoofdverpakking breedte: 500 mm, (Buitenste) hoofdverpakking lengte: 330 mm, (Buitenste) hoofdverpakking hoogte: 220 mm



Kenmerken		Eisen aan de omgeving	
Connector 1 vormfactor	Recht	Relatieve vochtigheid in bedrijf (V-V)	80 - 90 procent
Connector 2 vormfactor	Recht	Gewicht en omvang	
Snoerlengte *	1 m	Gewicht	38 g
Aansluiting 1 *	DisplayPort	Breedte	200 mm
Aansluiting 2 *	USB Type-C	Diepte	1000 mm
Aansluiting 1 type *	Mannelijk	Hoogte	11 mm
Aansluiting 2 type *	Mannelijk	Verpakking	
HDCP	✓	Aantal per verpakking	1 stuk(s)
HDCP versie	1.4/2.2	Breedte verpakking	200 mm
DisplayPort versie	1.4	Diepte verpakking	220 mm
HDR-ondersteuning	✓	Gewicht verpakking	48 g
Maximum resolutie	7680 x 4320 Pixels	Technische details	
Ondersteunde grafische resoluties	1024 x 768 (XGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA), 2560 x 1440, 2560 x 1600 (WQXGA), 3840 x 2160, 4096 x 2160, 7680 x 4320	Certificaten van naleving	RoHS
Bandwidth	32400 MB/s	Logistieke gegevens	
Maximale refresh snelheid	120 Hz	Code geharmoniseerd systeem (HS)	84733080
Kleur van het product	Zwart	(Buitenste) hoofdverpakking breedte	500 mm
Chipset	STM32F072CBY6TR	(Buitenste) hoofdverpakking lengte	330 mm
Ondersteunde audiokanalen	7.1	(Buitenste) hoofdverpakking hoogte	220 mm
Certificering	CE, FCC, REACH	Hoeveelheid per (buitenste) hoofdverpakking	90 stuk(s)
Eisen aan de omgeving			
Bedrijfstemperatuur (T-T)	5 - 35 °C		
Temperatuur bij opslag	-20 - 60 °C		



0065030881753



065030881753

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.